

Product Data Sheet

3/8/2025

Select Compact

UK - Myson



- High heat output
- Lightweight
- 4-tap connections
- Top grille & side panels standard
- Eco-friendly

Description

The Select Compact panel radiator is designed with a 33mm pitch for the most effective heat distribution. This radiator balances high performance and eco-friendly efficiency by minimizing water and steel usage. Available in various types and sizes, all with factory-fitted top grills and side panels, the Select Compact is perfect for both retrofit and new installations.

Area of Application

The Select Compact is ideal for 2-pipe pumped indirect domestic and commercial heating applications. It features a 33mm pitch for optimal design, impressive heat output at low water content, lightweight construction using 33% less steel, and is available in 222 sizes with 4-tap connections.

Selection Criteria

For selecting or calculating the thermal heat power output, please use our design service. For quick selection, use our brochure.

Basic User Instructions

Install the Select Compact radiator with the appropriate radiator valves or thermostatic radiator valves for room temperature control. Ensure all connections are secure and that the system is fully bled of air. Check for any potential leaks and verify that the radiator is heating evenly. Regular maintenance includes cleaning the grill and panels to prevent dust buildup and checking the system pressure. Ensure maximum safety by keeping the radiators clear of obstructions and avoid covering them to maintain optimal performance.

Prescription text specifiers

The Select Compact radiator is constructed with high-grade materials and designed for optimal efficiency. It features a 33mm pitch, maximizing heat output while minimizing water and steel use. This radiator is suitable for 2-pipe pumped indirect systems and comes in single, double, double panel extra, and triple convactor types. The range includes 222 sizes with 4-tap connections, ensuring a suitable fit for any space. Factory-fitted top grills and side panels come standard. The Select Compact complies with BS EN 442 and holds the BS Kitemark, offering a 10-year warranty for peace of mind.

Warranty

For your additional peace of mind, Purmo Group gives the following Warranty against manufacturing defect. Your statutory rights are not affected by this Warranty.

Subject as provided below, Purmo Group warrants to the original purchaser at the original installation site that its products will be free from defects in materials and workmanship for the following periods:

- Hydronic Radiators: 10 years from date of purchase.*
- Fan Assisted Radiators (ULOW-E2): 2 years from date of purchase.*
- Fan Convectors: 2 years from date of purchase.
- Hydronic Underfloor Heating: 10 years for the pipe from date of purchase.
- Hydronic Underfloor Heating: 2 years on accessories, actuators, ball valves, controls, expansion vessels, fittings, low loss headers, manifolds, mixer control groups & tooling from date of purchase.
- Hydronic Underfloor Heating: 12 months on all pumps from date of purchase.
- Electric Underfloor Heating: 10 years from date of purchase (except programmer & sensor).
- Electric Radiators: 10 years from date of purchase on radiator unit*, electric controls & electronic components; 2 years from date of purchase.*
- Electric Towel Warmers: 2 years from date of purchase.*
- Hydronic Towel Warmers: 5 to 10 years from date of purchase depending on product type.*
- Myson Radiator Valves and Controls: 2 to 5 years from date of purchase, depending on range.

*Products which are exposed to prolonged extreme conditions, such as high humidity or severe cold/condensation, may be subject to deterioration. This is not a result of any manufacturing defect.

Products installed in these circumstances will be subject to a warranty period of twelve months only.

The original purchaser's remedy for breach of this Warranty is expressly limited to repair or replacement of any part or parts found to be defective under conditions of normal service and use during the above Warranty period and does not extend to Purmo Group being liable for any incidental, special or consequential damages or losses whatsoever, such as loss of use of the product, inconvenience or lost profits.

This Warranty does not cover any defect, damage or malfunction in the product which is due to: failure to comply in any respect with Purmo Group's installation, maintenance or operating instructions; faulty storage,

handling, installation or repair; mis-use; neglect; accident; abuse; or general wear and tear.

Before this warranty can be activated, the original purchaser will be required to prove, with supporting documentation, the date and place of purchase, as Purmo Group may need to conduct its investigation into

the alleged defect. This should be within 28 days of the date when the defect was discovered or ought to have reasonably discovered the defect.

Purmo Group reserves the right to make a reasonable charge for inspecting and testing any product which is subject to a Warranty claim and the rights conferred by the Warranty are conditional upon the payment of such charge. The charge may be made, at Purmo Group's discretion, either before or after the inspection and testing of the product. In the event that it is established to Purmo Group's reasonable satisfaction that a valid Warranty claim has been made in respect of the product, then any inspection charge which has been paid will be refunded in full by Purmo Group.

Specification

Feature	Unit	Value
Etim Class		EC010047 - De-aeration valve (manual), EC010064 - Thermostatic control head for valve, EC010136 - Radiator stop valve, EC011022 - Panel radiator
Item weight	Kilogram (kg)	0.0037, 0.0077, 0.0112, 0.0182, 0.0368 ... 9.78, 9.84, 9.8966, 90.36, 94.6875
Surface protection		Chromium-plated, Untreated
Connection 1		External thread conical BSPT-R (ISO 7-1 / EN 10226-1)
Connection 2		Hose socket
Housing material		Brass, Bronze
Operation		Manually operated, Turn button
Max. operating pressure	Bar (bar)	8, 800
Size of threaded connection		1/8 inch (6)
Model		Other
Height	Millimetre (mm)	300, 400, 450, 500, 550, 600, 750, 900, 950
Shape		Right-angled, Straight
Automatic flow control		No
With straight tailpiece		Yes
Pressure independent		No
With dust cap		No
With compression set		No
Suitable for single pipe system		Yes
Suitable for two pipe system		Yes
Size of pipe connection		1/2 inch (15), 3/8 inch (10)
Size of radiator connection		1/2 inch (15)
Shortened construction length		No
Reverse direction of flow		Yes
Size of thermostatic adjustment element connection		M30 x 1.5
Can be preset		No
Presetting		None
Thermostatically prepared		Yes
With bent tailpiece		No
Colour		White
RAL-number		9016
Watt Per Meter	Watt per metre (W/m)	1018, 1156, 1221, 1230, 1340 ... 711, 761,

Feature	Unit	Value
Watt Per Meter	Watt per metre (W/m)	868, 961, 963
Mounting direction		Horizontal
Factor K		1.361, 10.071, 10.108, 10.313, 10.447 ... 9.747773, 9.756, 9.797, 9.846, 9.913
Heat emission according to EN 442 20 °C – 55/45 [Btu/h]		1007, 1010, 1017, 1018, 1063 ... 914, 932, 958, 9721, 998
Max. operating temperature	Degrees celsius (°C)	110
Number of wall brackets		2, 3
Heat emission according to EN 442 20 °C – 75/65 [Btu/h]		10011, 10031, 10496, 11109, 11123 ... 9192, 9330, 9393, 9646, 9721
Depth	Millimetre (mm)	1.02E+38, 102, 106, 152, 62, 70, 7E+37
Collapsible		No
Type		11, 21, 22, 33
Length	Millimetre (mm)	1000, 1100, 1200, 1300, 1400 ... 500, 600, 700, 800, 900
Material		Steel
Water content	Litre (l)	0.68, 1.02, 1.08, 1.1, 1.28 ... 9.8, 9.84, 9.9, 9.9375, 9.954
With mounting material		Yes
Water-bearing front panel		Yes
Surface structure front side panel		Profiled
Heat emission according to EN 442 20 °C Watt (W) – 55/45		1003, 1004.8, 1028, 1034, 1042 ... 967, 976, 976.8, 977, 989
Recessed towel holder		No
Connection 2, left side low		Inlet/outlet flow
Connection 3, left side top		Inlet flow
Connection 6, right side top		Inlet flow
Connection 7, right side low		Inlet/outlet flow
Number of standard connections		4
Welded-on strips		Yes
With drain valve		Yes
With de-aerator		Yes
With de-aeration connection		Yes
With drain possibility (connection)		Yes
Thread connection		Internal thread
With towel holder		No
Thread size (inch)		1/2 inch
Heat emission according to EN 442 20 °C Watt (W) – 75/65		1018, 1025, 1028, 1029, 1040 ... 964, 977, 983, 984, 995
N-exponent		1.2803, 1.294, 1.2981, 1.3026, 1.307 ... 1.346, 1.3486, 1.3515, 1.3543, 1.36
With side lining		Yes

Feature	Unit	Value
With single-point connection		No
With integrated thermostatic valve		No
With wall brackets		Yes
With blind stops		No
With top cladding		Yes
Heat emission according to EN 442 laboratory		Yes
Suitable for electrical element		No
With electrical element		No
Suitable for damp space		No
Standard colour		Yes
Degree of gloss		Glossy
Max. Operating Temperature	Degrees celsius (°C)	110
Weight	Kilogram (kg)	132.5625, 17.65, 18.8, 21.025, 21.18 ... 49.956, 50.46, 58.282, 69.56, 95.749
Mounting Direction		Horizontal

Resources

Document Description	Document Type	Link
Myson Complete Solutions - Full Brochure	Brochure	https://asset.productmarketingcloud.com/api/assetstorage/3577_24872a57-c3a5-4956-ab4b-dfa3b522c19b
Myson Select Compact Brochure	Brochure	https://asset.productmarketingcloud.com/api/assetstorage/3577_772bf2ae-de1e-4069-b99f-f600e86468af
	Installation Instructions	https://asset.productmarketingcloud.com/api/assetstorage/3577_3ba424c1-a325-43eb-8f23-5115c6c90420
Select Compact Wall and Floor Brackets	Installation Instructions	https://asset.productmarketingcloud.com/api/assetstorage/3577_e91d6cad-5f22-4649-b56b-bbdc62872ebc
	Brochure	https://asset.productmarketingcloud.com/api/assetstorage/3577_9ff67300-6b05-4198-aa4a-454110178f9c
Myson Panel Radiators - range brochure	Brochure	https://asset.productmarketingcloud.com/api/assetstorage/3577_67e51605-6ae8-4d51-a3cb-cc4625f0758f

Items

HVAC Code	Global Item Code	Item Description
	FDIG20015ABYBHUK0	Matchmate 15mm Lockshield Angle Chrome Drain Off
	FDII40015ABYBHUK0	Matchmate 15mm Wheelhead Angle Chrome C/W Pushfit 90 Degree Elbow
	FDII20B15AAYBHUK0	Matchmate 1/2"; Olive Wheelhead Straight Chrome
	FDIG10B15AAYBHUK0	Matchmate 1/2"; Olive Lockshield Straight Chrome
	FDII20015AAYBHUK0	Matchmate 15mm Wheelhead Straight Chrome
	FDII20010ABYBHUK0	Matchmate 10mm Wheelhead Angle Chrome
	FDIG10015AAYBHUK0	Matchmate 15mm Lockshield Straight Chrome
	FDII40010ABYBHUK0	Matchmate 10mm Wheelhead Angle Chrome C/W Pushfit 90 Degree Elbow
	FDIG90015ABYBHUK0	Matchmate 15mm Lockshield Angle Chrome Pushfit
	FDIG10010ABYBHUK0	Matchmate 10mm Lockshield Angle Chrome
	FDIG70010ABYBHUK0	Matchmate 10mm Lockshield Angle

HVAC Code	Global Item Code	Item Description
	FDIG70010ABYBHUK0	Chrome Drain Off Pushfit
	FDIG60010ABYBHUK0	Matchmate 10mm LS Angle Chrome Drain Off C/W Compression 90o Elbow
	FDIG20010ABYBHUK0	Matchmate 10mm Lockshield Angle Chrome Drain Off
	ADMY9000000YACUK3	Matchmate Wheelhead Top Only
	FDII30010ABYBHUK0	Matchmate 10mm Wheelhead Angle Chrome C/W Compression 90 Degree Elbow
	FDIG80015ABYBHUK0	Matchmate 15mm LS Angle Chrome Drain Off C/W Pushfit 90 Degree Elbow
	FDII10010ABYBHUK0	Matchmate 10mm Lockshield Angle Chrome C/W Pushfit 90 Degree Elbow
	FDIG10B15ABYBHUK0	Matchmate 1/2" ; Olive Lockshield Angle Chrome
	FDIG10015ABYBHUK0	Matchmate 15mm Lockshield Angle Chrome
	FDIG50010ABYBHUK0	Matchmate 10mm Lockshield Angle Chrome C/W Compression 90 Degree Elbow
	FDIG90010AAYBHUK0	Matchmate 10mm Lockshield Straight Chrome Pushfit
	FDIG80010ABYBHUK0	Matchmate 10mm LS Angle Chrome Drain Off C/W Pushfit 90 Degree Elbow
	FDII10015ABYBHUK0	Matchmate 15mm Lockshield Angle Chrome C/W Pushfit 90 Degree Elbow
	ADMY4000000YACUK3	Matchmaster Lockshield Top Only
	ADMY6000000YACUK3	Fullflow Lockshield & Wheelhead Tops Only
	FDI110010AAYBHUK0	Matchmaster 10mm Lockshield Straight Chrome Pushfit
	FDI110010ABYBHUK0	Matchmaster 10mm Lockshield Angle Chrome
	FDI110015AAYBHUK0	Matchmaster 15mm Lockshield Straight Chrome
	FDI110A15AAYBHUK0	Matchmaster 15mm Or 1/2" ; Bsp Lockshield Straight Chrome
	FDI110A15AAYBHUK1	Fullflow 15mm / 1/2" ; Copper Or 1/2" ; Bsp Lockshield Straight Chrome
	FDI110A15ABYBHUK0	Matchmaster 15mm Or 1/2" ; Bsp Lockshield Angle Chrome
	FDI110A15ABYBHUK1	Fullflow 15mm / 1/2" ; Copper Or

HVAC Code	Global Item Code	Item Description
	FDI110A15ABYBHUK1	1/2" Bsp Lockshield Angle Chrome
	FDI120010ABYBHUK0	Matchmaster 10mm Lockshield Angle Chrome Drain Off
	FDI120015ABYBHUK0	Matchmaster 15mm Lockshield Angle Chrome Drain Off
	FDI170015ABYBHUK0	Matchmaster 15mm Lockshield Angle Chrome Drain Off Pushfit
	FDI180010ABYBHUK0	Matchmaster 10mm LS Angle Chrome Drain Off C/W Pushfit 90 Degree Elbow
	FDI180015ABYBHUK0	Matchmaster 15mm LS Angle Chrome Drain Off C/W Pushfit 90 Degree Elbow
	FDI190010ABYBHUK0	Matchmaster 10mm Lockshield Angle Chrome Pushfit
	FDI210010AAYBHUK0	Matchmaster 10mm Lockshield Straight Chrome Pushfit 90 Degree Elbow
	FDI210010ABYBHUK0	Matchmaster 10mm Lockshield Angle Chrome C/W Pushfit 90 Degree Elbow
	FDI210015AAYBHUK0	Matchmaster 15mm LS Straight Chrome C/W Pushfit 90 Degree Elbow
	FDI210015ABYBHUK0	Matchmaster 15mm Lockshield Angle Chrome C/W Pushfit 90 Degree Elbow
	FDI220015AAYBHUK0	Matchmaster 15mm Wheelhead Straight Chrome
	FDI220015ABYBHUK0	Matchmaster 15mm Wheelhead Angle Chrome
	FDI220A15AAYBHUK0	Matchmaster 15mm Or 1/2" Bsp Wheelhead Straight Chrome
	FDI220A15AAYBHUK1	Fullflow 15mm / 1/2" Copper Or 1/2" Bsp Wheelhead Straight Chrome
	FDI220A15ABYBHUK1	Fullflow 15mm / 1/2" Copper Or 1/2" Bsp Wheelhead Angle Chrome
	FDI240010AAYBHUK0	Matchmaster 10mm Wheelhead Straight Chrome 90 Degree Elbow
	FDI240010ABYBHUK0	Matchmaster 10mm Wheelhead Angle Chrome C/W Pushfit 90 Degree Elbow
	FDII60015AAYBHUK1	Decorative 15mm LS Or Wheelhead Straight Polished Chrome - Traditional
	FDII60015ABYBHUK1	Decorative 15mm LS Or Wheelhead Angle Polished Chrome - Traditional
	FDII80010AAYBHUK1	Decorative 10mm LS Or WH Strght Polished Chrome C/W Pushfit 90o Elbow
	FDII80010ABYBHUK1	Decorative 10mm LS Or WH Angle

HVAC Code	Global Item Code	Item Description
	FDII80010ABYBHUK1	Polished Chrome C/W Pushfit 90o Elbow
	FDII80015AAYBHUK1	Decorative 15mm LS Or WH Strght Polished Chrome C/W Pushfit 90o Elbow
	FDII80015ABYBHUK1	Decorative 15mm LS Or WH Angle Polished Chrome C/W Pushfit 90o Elbow
	FDII90015AAYBHUK1	Decorative 15mm LS Or Wheelhead Straight Polished Chrome - Slimline
	FDII90015ABYBHUK1	Decorative 15mm LS Or Wheelhead Angle Polished Chrome - Slimline
	FDJG90015ABYBHOP0	Plus 15mm TRV Angle Chrome Pushfit
	FDJJ10010ABYBHOP0	Plus 10mm TRV Angle Chrome
	FDJJ10015ABYBHOP0	Plus 15mm TRV Angle Chrome
	FDJJ20010ABYBHUK0	Petite 10mm TRV angle chrome
	FDJJ20015AAYBHUK0	Petite 15mm TRV straight chrome
	FDJJ20015ABYBHUK0	Petite 15mm TRV angle chrome
	FDJJ30010ABYBHUK0	Petite 10mm TRV angle chrome c/w pushfit 90 degree elbow
	FDJJ30015ABYBHUK0	Petite 15mm TRV angle chrome c/w pushfit 90 degree elbow
	FDJN11510ABYBHUK0	TRV2 Radpack 10/15mm TRV2 & Matchmaster Lockshield Pack Angle Chrome
	FDJN20010ABYBHUK0	TRV2 Radpack 10mm TRV2 & Matchmate LS Pack Angle Chrome Pushfit
	FDJN20015ABYBHUK0	TRV2 Radpack 15mm TRV2 & Matchmate LS Pack Angle Chrome Pushfit
	FDJN30010ABYBHUK0	TRV2 Radpack 10mm TRV2 & Matchmate LS Pk Angle Chrome C/W PF 90o Elbow
	FDJN30015ABYBHUK0	TRV2 Radpack 15mm TRV2 & Matchmate LS Pk Angle Chrome C/W PF 90o Elbow
	FDJO30015AAYBHUK0	Petite Pack - 15mm Petite TRV & Matchmate LS straight chrome
	FDJO30015ABYBHUK0	Petite Pack - 15mm Petite TRV & Matchmate LS angle chrome
	FDJO40015ABYBHUK0	Petite Pack - 15mm Petite TRV & Matchmate LS angle chrome drain off
	FDJO50010ABYBHUK0	Petite Pack-10mm Petite TRV & Matchmate LS angle chrome DO-PF90 elbow
	FDJO60010ABYBHUK0	Petite Pack-10mm Petite TRV & Matchmate LS angle chrome - PF90 elbow
	FDJX10010AAYBHUK0	TRV2 10mm TRV Straight Chrome

HVAC Code	Global Item Code	Item Description
	FDJX10010ABYBHUKO	TRV2 10mm TRV Angle Chrome
	FDJX10015AAYBHUKO	TRV2 15mm TRV Straight Chrome
	FDJX10015ABYBHUKO	TRV2 15mm TRV Angle Chrome
	FDJX10A15ABYBOUKO	TRV 15mm Or 1/2" Bsp TRV Angle Chrome Body Only
	FDJX11518ABYBHUKO	TRV2 8/10/15mm TRV Angle Chrome
	FDJX20010ABYBHUKO	TRV2 10mm TRV Angle Chrome C/W Pushfit 90 Degree Elbow
	FDJX30010ABYBHUKO	TRV2 10mm TRV Angle Chrome C/W Compression 90 Degree Elbow
	FDJX30015ABYBHUKO	TRV2 15mm TRV Angle Chrome C/W Pushfit 90 Degree Elbow
	FDJX40010AAYBHUKO	TRV2 10mm TRV Straight Chrome Pushfit
	F062204011010N00	Type 22 400h x 1100w - Select Compact
	F061105004010N00	Type 11 500h x 400w - Select Compact
	F062104009010N00	Type 21 400h x 900w - Select Compact
	F063305023010N00	Type 33 500h x 2300w - Select Compact
	F062205024010N00	Type 22 500h x 2400w - Select Compact
	F062207509010N00	Type 22 750h x 900w - Select Compact
	F062103010010N00	Type 21 300h x 1000w - Select Compact
	F061106024010N00	Type 11 600h x 2400w - Select Compact
	F062104006010N00	Type 21 400h x 600w - Select Compact
	F061105006010N00	Type 11 500h x 600w - Select Compact
	F061105005010N00	Type 11 500h x 500w - Select Compact
	F062206010010N00	Type 22 600h x 1000w - Select Compact
	F061103020010N00	Type 11 300h x 2000w - Select Compact
	F062205012010N00	Type 22 500h x 1200w - Select Compact
	F062103014010N00	Type 21 300h x 1400w - Select Compact
	F062206016010N00	Type 22 600h x 1600w - Select Compact
	F063309014010N00	Type 33 900h x 1400w - Select Compact
	F062204016010N00	Type 22 400h x 1600w - Select Compact
	F063305012010N00	Type 33 500h x 1200w - Select Compact
	F062206013010N00	Type 22 600h x 1300w - Select Compact
	F062206011010N00	Type 22 600h x 1100w - Select Compact
	F063305008010N00	Type 33 500h x 800w - Select Compact
	F063306016010N00	Type 33 600h x 1600w - Select Compact
	F061107505010N00	Type 11 750h x 500w - Select Compact
	F062207507010N00	Type 22 750h x 700w - Select Compact
	F061106007010N00	Type 11 600h x 700w - Select Compact
	F062205008010N00	Type 22 500h x 800w - Select Compact
	F062106014010N00	Type 21 600h x 1400w - Select Compact

HVAC Code	Global Item Code	Item Description
	F062107504010N00	Type 21 750h x 400w - Select Compact
	F062205006010N00	Type 22 500h x 600w - Select Compact
	F062107506010N00	Type 21 750h x 600w - Select Compact
	F062205014010N00	Type 22 500h x 1400w - Select Compact
	F063307507010N00	Type 33 750h x 700w - Select Compact
	F062105008010N00	Type 21 500h x 800w - Select Compact
	F062204010010N00	Type 22 400h x 1000w - Select Compact
	F061103014010N00	Type 11 300h x 1400w - Select Compact
	F062106012010N00	Type 21 600h x 1200w - Select Compact
	F062204005010N00	Type 22 400h x 500w - Select Compact
	F061105016010N00	Type 11 500h x 1600w - Select Compact
	F063306011010N00	Type 33 600h x 1100w - Select Compact
	F063303018010N00	Type 33 300h x 1800w - Select Compact
	F062105014010N00	Type 21 500h x 1400w - Select Compact
	F062105012010N00	Type 21 500h x 1200w - Select Compact
	F061103004010N00	Type 11 300h x 400w - Select Compact
	F061107508010N00	Type 11 750h x 800w - Select Compact
	F062204018010N00	Type 22 400h x 1800w - Select Compact
	F063309009010N00	Type 33 900h x 900w - Select Compact
	F062203008010N00	Type 22 300h x 800w - Select Compact
	F062207504010N00	Type 22 750h x 400w - Select Compact
	F063306009010N00	Type 33 600h x 900w - Select Compact
	F063306010010N00	Type 33 600h x 1000w - Select Compact
	F062103006010N00	Type 21 300h x 600w - Select Compact
	F061104012010N00	Type 11 400h x 1200w - Select Compact
	F062203018010N00	Type 22 300h x 1800w - Select Compact
	F061106010010N00	Type 11 600h x 1000w - Select Compact
	F062204012010N00	Type 22 400h x 1200w - Select Compact
	F061106009010N00	Type 11 600h x 900w - Select Compact
	F062206006010N00	Type 22 600h x 600w - Select Compact
	F061105013010N00	Type 11 500h x 1300w - Select Compact
	F062104005010N00	Type 21 400h x 500w - Select Compact
	F061104009010N00	Type 11 400h x 900w - Select Compact
	F061103010010N00	Type 11 300h x 1000w - Select Compact
	F062206008010N00	Type 22 600h x 800w - Select Compact
	F063305018010N00	Type 33 500h x 1800w - Select Compact
	F062105007010N00	Type 21 500h x 700w - Select Compact
	F062105005010N00	Type 21 500h x 500w - Select Compact
	F061104014010N00	Type 11 400h x 1400w - Select Compact
	F061104006010N00	Type 11 400h x 600w - Select Compact
	F061106013010N00	Type 11 600h x 1300w - Select Compact

HVAC Code	Global Item Code	Item Description
	F061104013010N00	Type 11 400h x 1300w - Select Compact
	F061104010010N00	Type 11 400h x 1000w - Select Compact
	F063306007010N00	Type 33 600h x 700w - Select Compact
	F063306023010N00	Type 33 600h x 2300w - Select Compact
	F062207512010N00	Type 22 750h x 1200w - Select Compact
	F061107506010N00	Type 11 750h x 600w - Select Compact
	F063305006010N00	Type 33 500h x 600w - Select Compact
	F062106018010N00	Type 21 600h x 1800w - Select Compact
	F063307514010N00	Type 33 750h x 1400w - Select Compact
	F063306006010N00	Type 33 600h x 600w - Select Compact
	F062207510010N00	Type 22 750h x 1000w - Select Compact
	F062107516010N00	Type 21 750h x 1600w - Select Compact
	F062207506010N00	
	F061105024010N00	Type 11 500h x 2400w - Select Compact
	F062207516010N00	Type 22 750h x 1600w - Select Compact
	F062207514010N00	
	F061106011010N00	Type 11 600h x 1100w - Select Compact
	F061106014010N00	Type 11 600h x 1400w - Select Compact
	F063305014010N00	Type 33 500h x 1400w - Select Compact
	F061105010010N00	Type 11 500h x 1000w - Select Compact
	F062104010010N00	Type 21 400h x 1000w - Select Compact
	F063303006010N00	Type 33 300h x 600w - Select Compact
	F062205004010N00	Type 22 500h x 400w - Select Compact
	F062107514010N00	Type 21 750h x 1400w - Select Compact
	F063306008010N00	Type 33 600h x 800w - Select Compact
	F061106006010N00	Type 11 600h x 600w - Select Compact
	F062106005010N00	Type 21 600h x 500w - Select Compact
	F062204008010N00	Type 22 400h x 800w - Select Compact
	F062206020010N00	Type 22 600h x 2000w - Select Compact
	F063305009010N00	Type 33 500h x 900w - Select Compact
	F062205013010N00	Type 22 500h x 1300w - Select Compact
	F062107510010N00	
	F063305016010N00	Type 33 500h x 1600w - Select Compact
	F062206004010N00	Type 22 600h x 400w - Select Compact
	F062206009010N00	Type 22 600h x 900w - Select Compact
	F063305011010N00	Type 33 500h x 1100w - Select Compact
	F061107516010N00	Type 11 750h x 1600w - Select Compact
	F062106013010N00	Type 21 600h x 1300w - Select Compact
	F061107509010N00	Type 11 750h x 900w - Select Compact
	F062104008010N00	Type 21 400h x 800w - Select Compact
	F062106007010N00	Type 21 600h x 700w - Select Compact

HVAC Code	Global Item Code	Item Description
	F062103018010N00	Type 21 300h x 1800w - Select Compact
	F063305010010N00	Type 33 500h x 1000w - Select Compact
	F061103018010N00	Type 11 300h x 1800w - Select Compact
	F061104005010N00	Type 11 400h x 500w - Select Compact
	F062206005010N00	Type 22 600h x 500w - Select Compact
	F061104011010N00	Type 11 400h x 1100w - Select Compact
	F062205016010N00	Type 22 500h x 1600w - Select Compact
	F062106006010N00	Type 21 600h x 600w - Select Compact
	F062206018010N00	Type 22 600h x 1800w - Select Compact
	F061106016010N00	Type 11 600h x 1600w - Select Compact
	F063307506010N00	Type 33 750h x 600w - Select Compact
	F062104011010N00	Type 21 400h x 1100w - Select Compact
	F061105015010N00	Type 11 500h x 1500w - Select Compact
	F061105014010N00	Type 11 500h x 1400w - Select Compact
	F061104018010N00	Type 11 400h x 1800w - Select Compact
	F062105010010N00	Type 21 500h x 1000w - Select Compact
	F063307512010N00	Type 33 750h x 1200w - Select Compact
	F062106009010N00	Type 21 600h x 900w - Select Compact
	F061103024010N00	Type 11 300h x 2400w - Select Compact
	F061105007010N00	Type 11 500h x 700w - Select Compact
	F063309010010N00	Type 33 900h x 1000w - Select Compact
	F061107514010N00	Type 11 750h x 1400w - Select Compact
	F061105008010N00	Type 11 500h x 800w - Select Compact
	F062204014010N00	Type 22 400h x 1400w - Select Compact
	F063303012010N00	Type 33 300h x 1200w - Select Compact
	F063307508010N00	Type 33 750h x 800w - Select Compact
	F061105009010N00	Type 11 500h x 900w - Select Compact
	F062205007010N00	Type 22 500h x 700w - Select Compact
	F062206024010N00	Type 22 600h x 2400w - Select Compact
	F063303010010N00	Type 33 300h x 1000w - Select Compact
	F062106011010N00	Type 21 600h x 1100w - Select Compact
	F062204009010N00	Type 22 400h x 900w - Select Compact
	F062104014010N00	Type 21 400h x 1400w - Select Compact
	F061103006010N00	Type 11 300h x 600w - Select Compact
	F063307505010N00	Type 33 750h x 500w - Select Compact
	F062107508010N00	
	F062104016010N00	Type 21 400h x 1600w - Select Compact
	F062107505010N00	Type 21 750h x 500w - Select Compact
	F061106020010N00	Type 11 600h x 2000w - Select Compact
	F061106012010N00	Type 11 600h x 1200w - Select Compact
	F062105018010N00	Type 21 500h x 1800w - Select Compact

HVAC Code	Global Item Code	Item Description
	F062107512010N00	Type 21 750h x 1200w - Select Compact
	F062203006010N00	Type 22 300h x 600w - Select Compact
	F063306005010N00	Type 33 600h x 500w - Select Compact
	F062205015010N00	Type 22 500h x 1500w - Select Compact
	F063305020010N00	Type 33 500h x 2000w - Select Compact
	F061105020010N00	Type 11 500h x 2000w - Select Compact
	F061107504010N00	Type 11 750h x 400w - Select Compact
	F062106008010N00	Type 21 600h x 800w - Select Compact
	F062206007010N00	Type 22 600h x 700w - Select Compact
	F062205009010N00	Type 22 500h x 900w - Select Compact
	F062205020010N00	Type 22 500h x 2000w - Select Compact
	F061105011010N00	Type 11 500h x 1100w - Select Compact
	F062205005010N00	Type 22 500h x 500w - Select Compact
	F062203020010N00	Type 22 300h x 2000w - Select Compact
	F061107512010N00	Type 11 750h x 1200w - Select Compact
	F061104008010N00	Type 11 400h x 800w - Select Compact
	F062105006010N00	Type 21 500h x 600w - Select Compact
	F062106010010N00	Type 21 600h x 1000w - Select Compact
	F061106005010N00	Type 11 600h x 500w - Select Compact
	F063307510010N00	Type 33 750h x 1000w - Select Compact
	F062206014010N00	Type 22 600h x 1400w - Select Compact
	F061104016010N00	Type 11 400h x 1600w - Select Compact
	F063309012010N00	Type 33 900h x 1200w - Select Compact
	F061106008010N00	Type 11 600h x 800w - Select Compact
	F063309004010N00	Type 33 900h x 400w - Select Compact
	F062104013010N00	Type 21 400h x 1300w - Select Compact
	F062207505010N00	Type 22 750h x 500w - Select Compact
	F063307509010N00	Type 33 750h x 900w - Select Compact
	F063307504010N00	Type 33 750h x 400w - Select Compact
	F062104018010N00	Type 21 400h x 1800w - Select Compact
	F063303020010N00	Type 33 300h x 2000w - Select Compact
	F061107507010N00	Type 11 750h x 700w - Select Compact
	F062105016010N00	Type 21 500h x 1600w - Select Compact
	F063303014010N00	Type 33 300h x 1400w - Select Compact
	F063306020010N00	Type 33 600h x 2000w - Select Compact
	F061106018010N00	Type 11 600h x 1800w - Select Compact
	F062204006010N00	Type 22 400h x 600w - Select Compact
	F062104012010N00	Type 21 400h x 1200w - Select Compact
	F062203024010N00	Type 22 300h x 2400w - Select Compact
	F062203010010N00	Type 22 300h x 1000w - Select Compact
	F063309008010N00	Type 33 900h x 800w - Select Compact

HVAC Code	Global Item Code	Item Description
	F062105009010N00	Type 21 500h x 900w - Select Compact
	F063309005010N00	Type 33 900h x 500w - Select Compact
	F062205011010N00	Type 22 500h x 1100w - Select Compact
	F061106004010N00	Type 11 600h x 400w - Select Compact
	F063309007010N00	Type 33 900h x 700w - Select Compact
	F062203014010N00	Type 22 300h x 1400w - Select Compact
	F062106016010N00	Type 21 600h x 1600w - Select Compact
	F062204007010N00	Type 22 400h x 700w - Select Compact
	F062206012010N00	Type 22 600h x 1200w - Select Compact
	F062104007010N00	Type 21 400h x 700w - Select Compact
	F062105004010N00	Type 21 500h x 400w - Select Compact
	F062207508010N00	Type 22 750h x 800w - Select Compact
	F063306004010N00	Type 33 600h x 400w - Select Compact
	F063309006010N00	Type 33 900h x 600w - Select Compact
	F061105018010N00	Type 11 500h x 1800w - Select Compact
	F062106004010N00	Type 21 600h x 400w - Select Compact
	F063306012010N00	Type 33 600h x 1200w - Select Compact
	F061107510010N00	Type 11 750h x 1000w - Select Compact
	F062205010010N00	Type 22 500h x 1000w - Select Compact
	F061104007010N00	Type 11 400h x 700w - Select Compact
	F063306018010N00	Type 33 600h x 1800w - Select Compact
	F062204013010N00	Type 22 400h x 1300w - Select Compact
	F062107507010N00	Type 21 750h x 700w - Select Compact
	F062107509010N00	
	F063305007010N00	Type 33 500h x 700w - Select Compact
	F063306014010N00	Type 33 600h x 1400w - Select Compact
	F062205018010N00	Type 22 500h x 1800w - Select Compact
	F061105012010N00	Type 11 500h x 1200w - Select Compact
DEC15LWAC	FDII70015ABYBHUK1	
DEC15LWSC	FDII70015AAYBHUK1	
MASTER10WAC	FDI220010ABYBHUK0	
MASTER10WACPF	FDI250010ABYBHUK0	
MASTER151/2WAC	FDI220A15ABYBHUK0	
MASTER15LAC	FDI110015ABYBHUK0	
MASTERWHTOP	ADMY5000000YACUK3	
MATE1/2LACD	FDIG20B15ABYBHUK0	
MATE1/2WAC	FDII20B15ABYBHUK0	
MATE10LACPF	FDIG90010ABYBHUK0	
MATE10WACPF	FDII50010ABYBHUK0	
MATE15WAC	FDII20015ABYBHUK0	
MATE15WACPF	FDII50015ABYBHUK0	

HVAC Code	Global Item Code	Item Description
MATELSTOP	ADMY8000000YACUK3	
PETPAK1/2AC	FDJO30B15ABYBHUK0	
PETPAK10AC	FDJO30010ABYBHUK0	
PETPAK10ACD	FDJO40010ABYBHUK0	
SELKIT	AZ07MMPVKITUNI00	
TRV210SCPF90	FDJX30010AAYBHUK0	
TRV215SCPF90	FDJX20015AAYBHUK0	
TRV2PAK15AC	FDJN10015ABYBHUK0	