

Product Data Sheet

7/23/2025

Electronic Controls

Unisenza Plus Gateway

UK - Myson



- Integrated Zigbee 3.0 technology
- Connects up to 100 devices
- Easy installation
- Wireless and app integration
- Extended 5-year warranty

Description

The Myson Unisenza Plus Gateway is the central unit for connecting several Unisenza Plus devices to the cloud and an Internet router with a Wi-Fi or Ethernet cable connection. It is Zigbee 3.0 compatible with other products from the Unisenza Plus range, and connects up to 100 end devices such as intelligent room thermostats, electronic thermostatic heads (ETH) for radiators, receivers, sensors, etc. An extended warranty of 5 years applies to all Unisenza Plus products.

Area of Application

The Unisenza Plus Gateway is ideal for connecting Unisenza Plus devices to the cloud and an internet router using Wi-Fi or Ethernet cable. Suitable for up to 100 devices like intelligent room thermostats, electronic thermostatic heads for radiators, receivers, and sensors. Integration of the latest Zigbee 3.0 wireless technology ensuring comprehensive control over smart home heating and cooling systems.

Selection Criteria

For product selection or system calculation, please refer to our technical documents, product manuals, or use our design service. For quick selection, use our brochure.

Basic User Instructions

For complete instructions, visit www.myson.com. To control the Unisenza Plus Gateway, download the Unisenza Plus app from the App Store for iOS or Google Play. Ensure the gateway is connected to your internet router via Wi-Fi or Ethernet. It supports connecting up to 100 devices and integrates seamlessly with Zigbee 3.0 products.

Prescription text specifiers

The Unisenza Plus Gateway is the central unit for connecting Unisenza Plus devices to the cloud and an internet router using Wi-Fi or Ethernet cable. It supports up to 100 devices, including intelligent room thermostats, electronic thermostatic heads for radiators, receivers, and sensors. Fully compatible with Zigbee 3.0, it ensures seamless integration and optimal control of your smart heating and cooling systems. An extended 5-year warranty is provided for all Unisenza Plus products. For full installation and operation guidance, please consult the technical manuals and documentation available at www.myson.co.uk.

Warranty

For your additional peace of mind, Purmo Group gives the following Warranty against manufacturing defect. Your statutory rights are not affected by this Warranty.

Subject as provided below, Purmo Group warrants to the original purchaser at the original installation site that its products will be free from defects in materials and workmanship for the following periods:

- Hydronic Radiators: 10 years from date of purchase.*
- Fan Assisted Radiators (ULOW-E2): 2 years from date of purchase.*
- Fan Convectors: 2 years from date of purchase.
- Hydronic Underfloor Heating: 10 years for the pipe from date of purchase.
- Hydronic Underfloor Heating: 2 years on accessories, actuators, ball valves, controls, expansion vessels, fittings, low loss headers, manifolds, mixer control groups & tooling from date of purchase.
- Hydronic Underfloor Heating: 12 months on all pumps from date of purchase.
- Electric Underfloor Heating: 10 years from date of purchase (except programmer & sensor).
- Electric Radiators: 10 years from date of purchase on radiator unit*, electric controls & electronic components; 2 years from date of purchase.*
- Electric Towel Warmers: 2 years from date of purchase.*
- Hydronic Towel Warmers: 5 to 10 years from date of purchase depending on product type.*
- Myson Radiator Valves and Controls: 2 to 5 years from date of purchase, depending on range.

*Products which are exposed to prolonged extreme conditions, such as high humidity or severe cold/condensation, may be subject to deterioration. This is not a result of any manufacturing defect.

Products installed in these circumstances will be subject to a warranty period of twelve months only.

The original purchaser's remedy for breach of this Warranty is expressly limited to repair or replacement of any part or parts found to be defective under conditions of normal service and use during the above Warranty period and does not extend to Purmo Group being liable for any incidental, special or consequential damages or losses whatsoever, such as loss of use of the product, inconvenience or lost profits.

This Warranty does not cover any defect, damage or malfunction in the product which is due to: failure to comply in any respect with Purmo Group's installation, maintenance or operating instructions; faulty storage,

handling, installation or repair; mis-use; neglect; accident; abuse; or general wear and tear.

Before this warranty can be activated, the original purchaser will be required to prove, with supporting documentation, the date and place of purchase, as Purmo Group may need to conduct its investigation into

the alleged defect. This should be within 28 days of the date when the defect was discovered or ought to have reasonably discovered the defect.

Purmo Group reserves the right to make a reasonable charge for inspecting and testing any product which is subject to a Warranty claim and the rights conferred by the Warranty are conditional upon the payment of such charge. The charge may be made, at Purmo Group's discretion, either before or after the inspection and testing of the product. In the event that it is established to Purmo Group's reasonable satisfaction that a valid Warranty claim has been made in respect of the product, then any inspection charge which has been paid will be refunded in full by Purmo Group.

Specification

Feature	Unit	Value
Etim Class		EC001099 - System interface/media gateway for bus system
Bus system KNX		No
Bus system KNX-RF (Radio Frequent)		No
Bus system KNX Secure		No
Bus system KNX Secure-RF (Radio Frequency)		No
Bus system radio frequent		No
Bus system LON		No
Bus system Powernet		No
Other bus systems		Zigbee
Radio frequent bidirectional		No
Model		Ethernet interface, Multiple interface
Mounting method		Surface mounted
Number of channels		1
Max. number of devices per channel		32, 100
Demounting protection		No
With LED indication		Yes
Updateable		Yes
Operating voltage min	Volt (V)	5 - 12
Voltage type		DC
Power consumption	Watt (W)	3
Protocol		TCP/IP
Provider dependent		Yes
Visualization		No
Web-Server		No
Radio interface		No
IR interface		No
Degree of protection (IP)		IP30
Height	Millimetre (mm)	78, 95
Width / Length	Millimetre (mm)	90, 242
Depth	Millimetre (mm)	25, 256
Weight	Kilogram (kg)	0.15, 0.19

Resources

Document Description	Document Type	Link
----------------------	---------------	------

Items

Local Code	Global Item Code	Item Description
T2HUB	FDK-T2HUB	Touch2 Wifi Hub Only
UNIPLGATEWAY	FDZ5GTUBA1000013	Unisenza Plus Gateway