

Product Data Sheet

4/1/2025

Electronic Controls

Unisenza Digital Thermostat

UK - Myson



- Controls heating & cooling.
- Ultra-flat design.
- Intuitive, easy to use display.
- Optional floor sensor.
- Extended 5 year warranty.

Description

Myson Unisenza Digital Thermostat is an electronic PI controller (2-point or PWM) with silent Triac output and LCD display. Temperature range 5-30 °C. Click-mounting on flush-mounted connection unit. Suitable for heating and cooling and ECO operation, freely definable setback temperature; connection option for an external floor sensor. Ultra-flat design with only 17 mm depth. An extended warranty of 5 years applies to all Unisenza products.

Area of Application

The Unisenza Digital Thermostat is suitable for heating & cooling and ECO operation. It features an ultra-flat design with a temperature range of 5-30°C, selectable programme options (Comfort, ECO, Automatic, Manual), and optional connection for an external floor sensor.

Selection Criteria

For selecting the product or calculating the system, please use our technical documents, product manuals, our design service or contact us via email or phone.

Basic User Instructions

For the best use of the Unisenza Digital Thermostat, ensure it is mounted on a flush-mounted connection unit. It supports selectable programme options (Comfort, ECO, Automatic, Manual) and features freely definable setback temperatures. Compatible with additional external floor sensors, its ultra-flat design allows for easy integration. Regular updates and operation can be maintained through its LCD display. Extended warranty of 5 years applies.

Prescription text specifiers

Unisenza Digital InWall thermostat as an electronic PI controller (2-point or PWM) with noiseless Triac output and LCD display. It supports a temperature range of 5-30°C and click installation on a flush-mounted connection unit. Suitable for heating & cooling and ECO operation, it offers selectable programme options including Comfort, ECO, Automatic, and Manual modes. Features freely definable setback temperature and optional connection for an external floor sensor. The ultra-flat design has a depth of only 17 mm. Comes with an extended 5-year warranty.

Warranty

For your additional peace of mind, Purmo Group gives the following Warranty against manufacturing defect. Your statutory rights are not affected by this Warranty.

Subject as provided below, Purmo Group warrants to the original purchaser at the original installation site that its products will be free from defects in materials and workmanship for the following periods:

- Hydronic Radiators: 10 years from date of purchase.*
- Fan Assisted Radiators (ULOW-E2): 2 years from date of purchase.*
- Fan Convectors: 2 years from date of purchase.
- Hydronic Underfloor Heating: 10 years for the pipe from date of purchase.
- Hydronic Underfloor Heating: 2 years on accessories, actuators, ball valves, controls, expansion vessels, fittings, low loss headers, manifolds, mixer control groups & tooling from date of purchase.
- Hydronic Underfloor Heating: 12 months on all pumps from date of purchase.
- Electric Underfloor Heating: 10 years from date of purchase (except programmer & sensor).
- Electric Radiators: 10 years from date of purchase on radiator unit*, electric controls & electronic components; 2 years from date of purchase.*
- Electric Towel Warmers: 2 years from date of purchase.*
- Hydronic Towel Warmers: 5 to 10 years from date of purchase depending on product type.*
- Myson Radiator Valves and Controls: 2 to 5 years from date of purchase, depending on range.

*Products which are exposed to prolonged extreme conditions, such as high humidity or severe cold/condensation, may be subject to deterioration. This is not a result of any manufacturing defect.

Products installed in these circumstances will be subject to a warranty period of twelve months only.

The original purchaser's remedy for breach of this Warranty is expressly limited to repair or replacement of any part or parts found to be defective under conditions of normal service and use during the above Warranty period and does not extend to Purmo Group being liable for any incidental, special or consequential damages or losses whatsoever, such as loss of use of the product, inconvenience or lost profits.

This Warranty does not cover any defect, damage or malfunction in the product which is due to: failure to comply in any respect with Purmo Group's installation, maintenance or operating instructions; faulty storage,

handling, installation or repair; mis-use; neglect; accident; abuse; or general wear and tear.

Before this warranty can be activated, the original purchaser will be required to prove, with supporting documentation, the date and place of purchase, as Purmo Group may need to conduct its investigation into

the alleged defect. This should be within 28 days of the date when the defect was discovered or ought to have reasonably discovered the defect.

Purmo Group reserves the right to make a reasonable charge for inspecting and testing any product which is subject to a Warranty claim and the rights conferred by the Warranty are conditional upon the payment of such charge. The charge may be made, at Purmo Group's discretion, either before or after the inspection and testing of the product. In the event that it is established to Purmo Group's reasonable satisfaction that a valid Warranty claim has been made in respect of the product, then any inspection charge which has been paid will be refunded in full by Purmo Group.

Specification

Feature	Unit	Value
Etim Class		EC003263 - Smart thermostat
Regulation type on/off		No
Regulation type modulating		Yes
Communications protocol		Other
Type of power supply		230 V, 24 V
Connection		3-wire
With receiver		No
Measuring range min	Degrees celsius (°C)	-
External sensor		Yes
With thermal feedback		No
Control characteristic		PI
Adaptive (self-learning)		No
Suitable for heating		Yes
Number of heater outputs		1
Suitable for cooling		Yes
Number of cooler outputs		1
Ventilation		No
Differential value min	Kelvin (K)	-
Adjustable differential		Yes
Sensor/feeler type		Resistance sensor
Temperature readable		Yes
With display		Yes
Type of clock		Year clock
Clock model		Digital
Overtime switch		No
Optimisation		Yes
With tap water circuit		No
Operation		Button
Suitable for floor heating control		Yes
Suitable for district heating control		Yes
Remote operation possible		No
IFTTT support available		No
With presence perception		No
Weather-dependent control system		No
Number of switching programmes		5
Contact type		Change-over contact (NO/NC)
Max. contact voltage	Volt (V)	24, 230

Feature	Unit	Value
Max. contact load	Ampere (A)	0.4, 1.15
Degree of protection (IP)		IP30
Colour		White
RAL-number		9016
Width	Millimetre (mm)	85
Depth	Millimetre (mm)	45
Height	Millimetre (mm)	85
Class of the temperature control		II
Standby power consumption (solstandby)	Watt (W)	1
Weight	Kilogram (kg)	0.145

Resources

Document Description	Document Type	Link
Unisenza Brochure ENG	Brochure	https://asset.productmarketingcloud.com/api/assetstorage/3577_89ca48f5-6d06-4edf-aa44-d46cdb6852e8
Myson Electronic Controls Brochure	Brochure	https://asset.productmarketingcloud.com/api/assetstorage/3577_78d97484-be71-44b9-99b6-1c27006da595
Myson Complete Solutions - Full Brochure	Brochure	https://asset.productmarketingcloud.com/api/assetstorage/3577_24872a57-c3a5-4956-ab4b-dfa3b522c19b

Items

Local Code	Global Item Code	Item Description
50433	FFU0TAAFDNCCC313	Unisenza Digital 24v Thermostat
50432	FFU3TAAFDNCCC313	Unisenza Digital 230v Thermostat