

Product Data Sheet

7/23/2025

Towel Warmers

Interlude

UK - Myson



- Sleek practical design
- Optional dual fuel kit
- Selected RAL colours available
- Available in textured, metallic and shimmer metallic
- Suitable for hydronic heating systems

Description

Myson Interlude is an elegant flat tube towel radiator crafted from high-quality steel, offering a sleek and streamlined appearance. Available in selected RAL, metallic, and special metallic finishes, Interlude is suitable for hydronic heating systems and provides both style and functionality. Optional dual fuel available.

Area of Application

Suitable for domestic and commercial bathrooms, offices, and kitchens. This radiator is designed for 2-pipe pumped indirect heating systems. It is provided with brackets, an air vent, and a plug. Operates up to a pressure of 4 bar and with connections 2 x ½" BSP.

Selection Criteria

Available in selected RAL, metallic, and special metallic finishes. See our range of colours. For quick selection, use our brochure.

Basic User Instructions

Install the Interlude with Radiator Valves or Thermostatic Radiator Valves for room temperature control. In warmer months, the ECO 450 Dual Fuel Heater Kit can be used to operate the towel warmer without turning on the entire heating system. Do not cover air vents. Always ensure safety measures are followed during installation.

Prescription text specifiers

The Interlude flat tube towel radiator is designed for domestic and commercial use. It is crafted from steel and comes in selected RAL, metallic or special metallic finishes. The Interlude is suitable for 2-pipe pumped indirect heating systems and has a working pressure up to 4 bar. Connections are 2 x ½" BSP as standard. The radiator can be installed with Radiator Valves or Thermostatic Radiator Valves for room temperature control. An ECO 450 Dual Fuel Heater Kit is available, allowing the heater to be used during warmer months without activating the entire system. Each unit includes brackets, an air vent, and a plug.

Warranty

For your additional peace of mind, Purmo Group gives the following Warranty against manufacturing defect. Your statutory rights are not affected by this Warranty.

Subject as provided below, Purmo Group warrants to the original purchaser at the original installation site that its products will be free from defects in materials and workmanship for the following periods:

- Hydronic Radiators: 10 years from date of purchase.*
- Fan Assisted Radiators (ULOW-E2): 2 years from date of purchase.*
- Fan Convectors: 2 years from date of purchase.
- Hydronic Underfloor Heating: 10 years for the pipe from date of purchase.
- Hydronic Underfloor Heating: 2 years on accessories, actuators, ball valves, controls, expansion vessels, fittings, low loss headers, manifolds, mixer control groups & tooling from date of purchase.
- Hydronic Underfloor Heating: 12 months on all pumps from date of purchase.
- Electric Underfloor Heating: 10 years from date of purchase (except programmer & sensor).
- Electric Radiators: 10 years from date of purchase on radiator unit*, electric controls & electronic components; 2 years from date of purchase.*
- Electric Towel Warmers: 2 years from date of purchase.*
- Hydronic Towel Warmers: 5 to 10 years from date of purchase depending on product type.*
- Myson Radiator Valves and Controls: 2 to 5 years from date of purchase, depending on range.

*Products which are exposed to prolonged extreme conditions, such as high humidity or severe cold/condensation, may be subject to deterioration. This is not a result of any manufacturing defect.

Products installed in these circumstances will be subject to a warranty period of twelve months

only.

The original purchaser's remedy for breach of this Warranty is expressly limited to repair or replacement of any part or parts found to be defective under conditions of normal service and use during the above Warranty period and does not extend to Purmo Group being liable for any incidental, special or consequential damages or losses whatsoever, such as loss of use of the product, inconvenience or lost profits.

This Warranty does not cover any defect, damage or malfunction in the product which is due to: failure to comply in any respect with Purmo Group's installation, maintenance or operating instructions; faulty storage,

handling, installation or repair; mis-use; neglect; accident; abuse; or general wear and tear.

Before this warranty can be activated, the original purchaser will be required to prove, with supporting documentation, the date and place of purchase, as Purmo Group may need to conduct its investigation into

the alleged defect. This should be within 28 days of the date when the defect was discovered or ought to have reasonably discovered the defect.

Purmo Group reserves the right to make a reasonable charge for inspecting and testing any product which is subject to a Warranty claim and the rights conferred by the Warranty are conditional upon the payment of such charge. The charge may be made, at Purmo Group's discretion, either before or after the inspection and testing of the product. In the event that it is established to Purmo Group's reasonable satisfaction that a valid Warranty claim has been made in respect of the product, then any inspection charge which has been paid will be refunded in full by Purmo Group.

Specification

Feature	Unit	Value
Etim Class		EC011023 - Tube radiator
Material		Steel
Material quality		Other
Number of tubes		6, 10, 16
Height	Millimetre (mm)	530, 905, 1655
Length	Millimetre (mm)	500
Depth	Millimetre (mm)	102
Depth from wall to front side min	Millimetre (mm)	102 - 117
Shape of radiation tube		Rectangular
Shape of collector		Round
Installation		Vertical
Radiant tube		Horizontal
Radiator design		Straight
Towel radiator model		Yes
Heat emission according to EN 442 20 °C Watt (W) - 55/45		161, 254, 435
Heat emission according to EN 442 20 °C Watt (W) - 75/65		470, 815
Heat emission according to EN 442 20 °C Watt (W) - 70/40		151, 490, 645, 1957
N-exponent		1.19, 1.205, 1.227
Max. operating pressure	Bar (bar)	4
Water content	Litre (l)	3, 5, 9
With fan heater		No
Max. input power heating	Watt (W)	300, 500, 1000
Standard colour		Yes
Colour		White
RAL-number		9016
Degree of gloss		Glossy
Surface protection		Lacquered
Suitable for damp space		Yes
With towel holder		No
With mirror		No
Mounting method		On wall
With side lining		No
With top cladding		No
Swivelling		No
Applicable with hot tap water circuit		No

Feature	Unit	Value
Number of standard connections		2
Connection 1, bottom left		Inlet/outlet flow
Connection 8, bottom right		Double connection, inlet-outlet
Thread size (inch)		1/2 inch
With single-point connection		No
Thread connection		Internal thread
With de-aeration connection		Yes
With de-aerator		Yes
With drain possibility (connection)		Yes
With drain valve		No
With integrated thermostatic valve		No
With consoles		Yes
With blind stops		Yes
With mounting material		Yes
Mounting Direction		Vertical
Factor K		4.215, 6.707
Heat emission according to EN 442 20 °C – 55/45 [Btu/h]		549, 867, 1484
Max. Operating Temperature	Degrees celsius (°C)	110
Number of wall brackets		4
Heat emission according to EN 442 20 °C – 75/65 [Btu/h]		1007, 1604, 2788
Watt Absolute	Watt (W)	295, 470, 815
Weight	Kilogram (kg)	8.8445, 11, 19

Resources

Document Description	Document Type	Link
Myson Contemporary Towel Warmer Range Brochure	Brochure	https://asset.productmarketingcloud.com/api/assetstorage/3577_ae11a75b-1ad9-4356-a6c2-b287c1d6c94c
Myson Interlude Brochure	Brochure	https://asset.productmarketingcloud.com/api/assetstorage/3577_55815816-8de5-43a5-ba0c-d86f3634673b
Myson Complete Solutions - Full Brochure	Brochure	https://asset.productmarketingcloud.com/api/assetstorage/3577_24872a57-c3a5-4956-ab4b-dfa3b522c19b
Myson Towel Warmer Accessory Brochure	Brochure	https://asset.productmarketingcloud.com/api/assetstorage/3577_4fe4000e-8d2d-4051-b8f8-c369afc56a1a
Colour options	Brochure	https://asset.productmarketingcloud.com/api/assetstorage/3577_f65456e4-6139-44cf-9d1d-0515ae484ab6
Myson Towel Warmers - range brochure	Brochure	https://asset.productmarketingcloud.com/api/assetstorage/3577_5781fce0-5efe-4895-b2bb-1b6f125c165b

Items

Local Code	Global Item Code	Item Description
INT1W	F8GA006005000120	White 530h x 500w - Interlude
INT1SILVER	F8GA00600500012R9006	Silver 530h x 500w - Interlude
INT2W	F8GA009005000120	White 905h x 500w - Interlude
INT2SILVER	F8GA00900500012R9006	Silver 905h x 500w - Interlude
INT3W	F8GA016505000120	White 1655h x 500w - Interlude
INT3SILVER	F8GA01650500012R9006	Silver 1655h x 500w - Interlude