Product Data Sheet 12/17/2024

Towel Warmers

Fatala

UK - Myson



- Asymmetric design
- Ample room for towels
- Various colour options
- Special finishes
- Hydronic system compatibility

Description

Introduce contemporary elegance into your home with a Myson Fatala Towel Radiator. Its attractive yet simple assymetric design is both stylish and practical, and will add a fresh modern look to any bathroom or living room. Suitable for hydronic heating systems.

Area of Application

Fatala is ideal for modern bathrooms and living rooms, providing both style and functionality. It is suitable for hydronic heating systems, with 2-pipe pumped indirect application. It offers ample space for drying towels and comes in multiple colours, including special finishes like metallic and shimmer metallic.

Selection Criteria

Various colours are available in addition to any RAL colours. For selection or calculation, use our design service or brochure.

Basic User Instructions

Install the Fatala towel radiator with Radiator Valves or Thermostatic Radiator Valves for optimal room temperature control. Ensure proper side or bottom connection using the 4 x ½" BSP standard fittings. Follow installation guidelines for hydronic systems. Regularly check connections and maintain the radiator to ensure long-term performance.

Prescription text specifiers

The Fatala towel radiator introduces contemporary elegance with an attractive asymmetric design. It is available in multiple colours, including RAL and special finishes like metallic and shimmer metallic. Suitable for 2-pipe pumped indirect domestic and commercial heating applications, it features $4 \times \frac{1}{2}$ BSP standard side or bottom connections. Manufactured from steel, it is tested to BS EN 442 and carries the CE & UKCA Mark. Operating pressures are tested up to 13 bar with a working pressure of up to 10 bar. Accessories include brackets, air vent, and plug. The product comes with a 10-year guarantee against manufacturing defects. Delivery time for non-stocked items is 4 - 6 weeks.

Warranty

For your additional peace of mind, Purmo Group gives the following Warranty against manufacturing defect. Your statutory rights are not affected by this Warranty. Subject as provided below, Purmo Group warrants to the original purchaser at the original installation site that its products will be free from defects in materials and workmanship for the following periods:

- Hydronic Radiators: 10 years from date of purchase.*
- Fan Assisted Radiators (ULOW-E2): 2 years from date of purchase.*
- Fan Convectors: 2 years from date of purchase.
- Hydronic Underfloor Heating: 10 years for the pipe from date of purchase.
- Hydronic Underfloor Heating: 2 years on accessories, actuators, ball valves, controls, expansion vessels, fittings, low loss headers, manifolds, mixer control groups & toolingfrom date of purchase.
- Hydronic Underfloor Heating: 12 months on all pumps from date of purchase.
- Electric Underfloor Heating: 10 years from date of purchase (except programmer & sensor).
- Electric Radiators and Towel Warmers: 2 years from date of purchase.*
- Hydronic Towel Warmers: 5 to 10 years from date of purchase depending on product type.*
- Myson Radiator Valves and Controls: 2 to 5 years from date of purchase, depending on range.
- *Products which are exposed to prolonged extreme conditions, such as high humidity or severe cold/condensation, may be subject to deterioration. This is not a result of any manufacturing defect. Products installed in these circumstances will be subject to a warranty period of twelve months only.

The original purchaser's remedy for breach of this Warranty is expressly limited to repair or replacement of any part or parts found to be defective under conditions of normal service and use during the above Warranty period and does not extend to Purmo Group being liable for any incidental, special or consequential damages or losses whatsoever, such as loss of use of the product, inconvenience or lost profits.

This Warranty does not cover any defect, damage or malfunction in the product which is due to: failure to comply in any respect with Purmo Group's installation, maintenance or operating instructions; faulty storage,

handling, installation or repair; mis-use; neglect; accident; abuse; or general wear and tear. Before this warranty can be activated, the original purchaser will be required to prove, with supporting documentation, the date and place of purchase, as Purmo Group may need to conduct its investigation into

the alleged defect. This should be within 28 days of the date when the defect was discovered or ought to have reasonably discovered the defect.

Purmo Group reserves the right to make a reasonable charge for inspecting and testing any product which is subject to a Warranty claim and the rights conferred by the Warranty are conditional upon the payment of such charge. The charge may be made, at Purmo Group's discretion, either before or after the inspection and testing of the product. In the event that it is established to Purmo Group's reasonable satisfaction that a valid Warranty claim has been made in respect of the product, then any inspection charge which has been paid will be refunded in full by Purmo Group.

Specification

Feature	Unit	Value
Etim Class		EC011023 - Tube radiator
Material		Steel
Material quality		Other
Number of tubes		20, 30, 44
Height	Millimetre (mm)	796, 1196, 1756
Length	Millimetre (mm)	500
Depth	Millimetre (mm)	87
Depth from wall to front side min	Millimetre (mm)	97 - 109
Shape of radiation tube		Round
Shape of collector		Round
Installation		Vertical
Radiant tube		Horizontal
Radiator design		Straight
Towel radiator model		Yes
Heat emission according to EN 442 20 - 55/45	O°C Watt (W)	243, 352, 476
Heat emission according to EN 442 20 - 75/65	O°C Watt (W)	446, 650, 897
N-exponent		1.1885, 1.202, 1.2414
Max. operating pressure	Bar (bar)	10
Water content	Litre (l)	3.8, 5.9, 8
With fan heater		No
Standard colour		Yes
Colour		White
RAL-number		9016
Degree of gloss		Glossy
Surface protection		Lacquered
Suitable for damp space		Yes
With towel holder		No
With mirror		No
Mounting method		On wall
With side lining		No
With top cladding		No
Swivelling		No
Applicable with hot tap water circuit		No
Number of standard connections		2
Connection TC, top center		Double connection, inlet-outlet
Thread size (inch)		1/2 inch
4 Product Data Sheet Fatala, 12/17/2024		

^{4 |} Product Data Sheet Fatala, 12/17/2024

Feature	Unit	Value
With single-point connection		No
Thread connection		Internal thread
With de-aeration connection		Yes
With de-aerator		Yes
With drain possibility (connection)		Yes
With drain valve		No
With integrated thermostatic valve		No
With consoles		Yes
Suitable for electrical element		No
With blind stops		Yes
With mounting material		Yes
Mounting direction		Vertical
Factor K		4.267, 5.899, 6.977
Heat emission according to EN 442 20 °C – 55/45 [Btu/h]		829, 1201, 1624
Max. operating temperature	Degrees celsius (°C)	110
Number of wall brackets		4
Variant		Straight
Heat emission according to EN 442 20 °C		1522, 2218, 3061
– 75/65 [Btu/h]		
Watt Absolute	Watt (W)	446, 650, 897
Item weight	Kilogram (kg)	8.9, 13.3, 19.5

Resources

Document Description	Document Type	Link
Myson Contemporary Towel Warmer Range Brochure	Brochure	https://asset.productmarketingcloud.co m/api/assetstorage/3577_ae11a75b-1ad 9-4356-a6c2-b287c1d6c94c
Myson Fatala Brochure	Brochure	https://asset.productmarketingcloud.com/api/assetstorage/3577_e2aff3b9-b8c9-4c35-a9cc-7804b3d0a2a7
Myson Complete Solutions - Full Brochure	Brochure	https://asset.productmarketingcloud.co m/api/assetstorage/3577_24872a57-c3a 5-4956-ab4b-dfa3b522c19b
Myson Towel Warmer Accessory Brochure	Brochure	https://asset.productmarketingcloud.co m/api/assetstorage/3577_4fe4000e-8d2 d-4051-b8f8-c369afc56a1a
Colour options	Brochure	https://asset.productmarketingcloud.co m/api/assetstorage/3577_f65456e4-613 9-44cf-9d1d-0515ae484ab6
Myson Towel Warmers - range brochure Brochure		https://asset.productmarketingcloud.co m/api/assetstorage/3577_5781fce0-5efe -4895-b2bb-1b6f125c165b

Items

Local Code	Global Item Code	Item Description	
MAE1W	F4BA008005000010	796h x 500w - Fatala	
MAE2W	F4BA012005000010	1196h x 500w - Fatala	
MAE3W	F4BA018005000010	1756h x 500w - Fatala	