


Product Data Sheet

1/27/2025

Awe

UK - Myson



- Traditional style towel warmer
- Floor standing
- Dual fuel options
- Integrated air vents
- Highly polished chrome plated finish

Description

Myson Awe is a floor standing towel warmer with an attractive and distinguished design. Manufactured from quality brass with a highly polished chrome plated finish, the Awe is a floor standing traditional towel warmer that makes a stylish addition to any bathroom. Suitable for hydronic heating systems, and optional dual fuel.

Area of Application

Awe is perfect for traditional style towel warming applications in both domestic and commercial settings. It works with 2-pipe pumped indirect and direct heating systems. Comes with 2 x ½" BSP connections and can be paired with a Dual Fuel Heater Kit for additional functionality during warmer months.

Selection Criteria

Range of sizes and heat outputs available.

Basic User Instructions

Install the Awe using Radiator Valves or Thermostatic Radiator Valves for room temperature regulation. For use during warmer months when central heating is off, install PTC Dual Fuel Heater Kits. Ensure the unit is properly connected to the heating system and air vents are integrated as instructed.

Prescription text specifiers

Awe is an attractive and distinguished floor-standing towel warmer, ideal for traditional settings. Made from high-quality brass and finished with a polished chrome plate, it is suitable for both domestic and commercial 2-pipe pumped indirect or direct heating systems. The unit includes 2 x ½" BSP connections, integrated air vents, and is compatible with PTC Dual Fuel Heater Kits for extra functionality in warmer months. Certified to BS EN 442 & EN 442 standards, Awe carries both CE & UKCA marks, ensuring high-quality and safety. The product is backed by a 10-year guarantee against manufacturing defects.

Warranty

For your additional peace of mind, Purmo Group gives the following Warranty against manufacturing defect. Your statutory rights are not affected by this Warranty.

Subject as provided below, Purmo Group warrants to the original purchaser at the original installation site that its products will be free from defects in materials and workmanship for the following periods:

- Hydronic Radiators: 10 years from date of purchase.*
- Fan Assisted Radiators (ULOW-E2): 2 years from date of purchase.*
- Fan Convectors: 2 years from date of purchase.
- Hydronic Underfloor Heating: 10 years for the pipe from date of purchase.
- Hydronic Underfloor Heating: 2 years on accessories, actuators, ball valves, controls, expansion vessels, fittings, low loss headers, manifolds, mixer control groups & tooling from date of purchase.
- Hydronic Underfloor Heating: 12 months on all pumps from date of purchase.
- Electric Underfloor Heating: 10 years from date of purchase (except programmer & sensor).
- Electric Radiators and Towel Warmers: 2 years from date of purchase.*
- Hydronic Towel Warmers: 5 to 10 years from date of purchase depending on product type.*
- Myson Radiator Valves and Controls: 2 to 5 years from date of purchase, depending on range.

*Products which are exposed to prolonged extreme conditions, such as high humidity or severe cold/condensation, may be subject to deterioration. This is not a result of any manufacturing defect. Products installed in these circumstances will be subject to a warranty period of twelve months only.

The original purchaser's remedy for breach of this Warranty is expressly limited to repair or replacement of any part or parts found to be defective under conditions of normal service and use during the above Warranty period and does not extend to Purmo Group being liable for any

incidental, special or consequential damages or losses whatsoever, such as loss of use of the product, inconvenience or lost profits.

This Warranty does not cover any defect, damage or malfunction in the product which is due to: failure to comply in any respect with Purmo Group's installation, maintenance or operating instructions; faulty storage,

handling, installation or repair; mis-use; neglect; accident; abuse; or general wear and tear.

Before this warranty can be activated, the original purchaser will be required to prove, with supporting documentation, the date and place of purchase, as Purmo Group may need to conduct its investigation into

the alleged defect. This should be within 28 days of the date when the defect was discovered or ought to have reasonably discovered the defect.

Purmo Group reserves the right to make a reasonable charge for inspecting and testing any product which is subject to a Warranty claim and the rights conferred by the Warranty are conditional upon the payment of such charge. The charge may be made, at Purmo Group's discretion, either before or after the inspection and testing of the product. In the event that it is established to Purmo Group's reasonable satisfaction that a valid Warranty claim has been made in respect of the product, then any inspection charge which has been paid will be refunded in full by Purmo Group.

Specification

Feature	Unit	Value
Etim Class		EC010048 - Accessories/spare parts for radiator fittings, EC011023 - Tube radiator
Mounting direction		Horizontal
Heat emission according to EN 442 20 °C – 55/45 [Btu/h]		403
Max. operating temperature	Degrees celsius (°C)	110
Item weight	Kilogram (kg)	0.45, 10.5
Heat emission according to EN 442 20 °C – 75/65 [Btu/h]		761
Watt Absolute	Watt (W)	223
Mounting method		On wall
Colour		White
Height	Millimetre (mm)	955
Depth	Millimetre (mm)	140
RAL-number		9016
Surface protection		Lacquered
Swivelling		No
Material quality		Other
Number of tubes		8
Length	Millimetre (mm)	693
Material		Steel
With mounting material		Yes
Heat emission according to EN 442 20 °C Watt (W) - 70/40		441
Applicable with hot tap water circuit		No
Heat emission according to EN 442 20 °C Watt (W) - 55/45		118
Towel radiator model		Yes
Connection 1, bottom left		Inlet/outlet flow
Connection 8, bottom right		Inlet/outlet flow
Number of standard connections		2
With fan heater		No
With drain valve		No
With de-aerator		Yes
With de-aeration connection		Yes
Max. operating pressure	Bar (bar)	6
Installation		Vertical
With drain possibility (connection)		Yes

Feature	Unit	Value
Thread connection		Internal thread
With towel holder		No
Thread size (inch)		1/2 inch
Heat emission according to EN 442 20 °C Watt (W) - 75/65		223
N-exponent		1.2397
With side lining		No
With single-point connection		No
With integrated thermostatic valve		No
With blind stops		Yes
Shape of radiation tube		Round
Depth from wall to front side	Millimetre (mm)	124 - 140
With top cladding		No
Shape of collector		Round
Radiant tube		Horizontal
Radiator design		Straight
With mirror		No
With consoles		Yes
Suitable for damp space		Yes
Standard colour		Yes
Degree of gloss		Glossy

Resources

Document Description	Document Type	Link
Myson Awe Brochure	Brochure	https://asset.productmarketingcloud.com/api/assetstorage/3577_0c5f3f42-2c21-4799-8963-71acce792c4
Myson Complete Solutions - Full Brochure	Brochure	https://asset.productmarketingcloud.com/api/assetstorage/3577_24872a57-c3a5-4956-ab4b-dfa3b522c19b
Myson Towel Warmer Accessory Brochure	Brochure	https://asset.productmarketingcloud.com/api/assetstorage/3577_4fe4000e-8d2d-4051-b8f8-c369afc56a1a
Myson Traditional Towel Warmer Range Brochure	Brochure	https://asset.productmarketingcloud.com/api/assetstorage/3577_142fc909-d562-4ad4-97b1-1f7e115b8e9a
Myson Towel Warmers - range brochure	Brochure	https://asset.productmarketingcloud.com/api/assetstorage/3577_5781fce0-5efe-4895-b2bb-1b6f125c165b

Items

Global Item Code	Item Description
AZ1-MTZDISCREETC	Discreet Wire Kit
F63-MTAB27C1	955h x 693w - Awe