

# Product Data Sheet

9/11/2025

Towel Warmers

## Dee

UK - Myson



- Radiator and towel rail combi
- High-quality chrome finish
- Traditional design
- Dual fuel kit available
- High heat output

## Description

The Myson Dee is a high quality, floor-standing combination radiator and towel rail that will add a classic, vintage feel to your bathroom. The stylish column radiator nestled in between a traditional elegant chrome frame offers you the best of both worlds; high heat output and a convenient heated towel rail. Suitable for hydronic heating systems, and optional dual fuel.

## Area of Application

Traditional style towel warmer made of high-quality brass. Ideal for both domestic and commercial heating applications using a 2-pipe pumped indirect system. Can be equipped with a Dual Fuel Heater Kit for use during warmer months.

## Selection Criteria

Range of sizes and heat outputs available. For detailed selection, use our brochure or design service.

## Basic User Instructions

Install the Dee with Radiator Valves or Thermostatic Radiator Valves to control room temperature. For use in warmer months without activating the entire heating system, install a PTC Dual Fuel Heater Kit, which is self-regulating.

## Prescription text specifiers

The Dee offers a high-quality combination of a column radiator and towel rail, made of steel and brass with a polished chrome finish. Suitable for domestic and commercial 2-pipe indirect systems. Comes with brackets, air vent, and plug. Can be equipped with a PTC Dual Fuel Heater Kit for year-round use. Available in multiple sizes and heat outputs, manufactured and tested to BS EN 442 standards. With a working pressure up to 7.4 bar and integrated air vents, the Dee combines classic style with modern efficiency. Ideal for achieving a vintage bathroom feel. 10-year warranty from purchase date.

If you need further customization or additional information, feel free to ask!

## Warranty

For your additional peace of mind, Purmo Group gives the following Warranty against manufacturing defect. Your statutory rights are not affected by this Warranty.

Subject as provided below, Purmo Group warrants to the original purchaser at the original installation site that its products will be free from defects in materials and workmanship for the following periods:

- Hydronic Radiators: 10 years from date of purchase.\*
- Fan Assisted Radiators (ULOW-E2): 2 years from date of purchase.\*
- Fan Convectors: 2 years from date of purchase.
- Hydronic Underfloor Heating: 10 years for the pipe from date of purchase.
- Hydronic Underfloor Heating: 2 years on accessories, actuators, ball valves, controls, expansion vessels, fittings, low loss headers, manifolds, mixer control groups & tooling from date of purchase.
- Hydronic Underfloor Heating: 12 months on all pumps from date of purchase.
- Electric Underfloor Heating: 10 years from date of purchase (except programmer & sensor).
- Electric Radiators: 10 years from date of purchase on radiator unit\*, electric controls & electronic components; 2 years from date of purchase.\*
- Electric Towel Warmers: 2 years from date of purchase.\*
- Hydronic Towel Warmers: 5 to 10 years from date of purchase depending on product type.\*
- Myson Radiator Valves and Controls: 2 to 5 years from date of purchase, depending on range.

\*Products which are exposed to prolonged extreme conditions, such as high humidity or severe cold/condensation, may be subject to deterioration. This is not a result of any manufacturing defect. Products installed in these circumstances will be subject to a warranty period of twelve months only.

The original purchaser's remedy for breach of this Warranty is expressly limited to repair or

replacement of any part or parts found to be defective under conditions of normal service and use during the above Warranty period and does not extend to Purmo Group being liable for any incidental, special or consequential damages or losses whatsoever, such as loss of use of the product, inconvenience or lost profits.

This Warranty does not cover any defect, damage or malfunction in the product which is due to: failure to comply in any respect with Purmo Group's installation, maintenance or operating instructions; faulty storage,

handling, installation or repair; mis-use; neglect; accident; abuse; or general wear and tear.

Before this warranty can be activated, the original purchaser will be required to prove, with supporting documentation, the date and place of purchase, as Purmo Group may need to conduct its investigation into

the alleged defect. This should be within 28 days of the date when the defect was discovered or ought to have reasonably discovered the defect.

Purmo Group reserves the right to make a reasonable charge for inspecting and testing any product which is subject to a Warranty claim and the rights conferred by the Warranty are conditional upon the payment of such charge. The charge may be made, at Purmo Group's discretion, either before or after the inspection and testing of the product. In the event that it is established to Purmo Group's reasonable satisfaction that a valid Warranty claim has been made in respect of the product, then any inspection charge which has been paid will be refunded in full by Purmo Group.

# Specification

| Feature                                                     | Unit            | Value                    |
|-------------------------------------------------------------|-----------------|--------------------------|
| Etim Class                                                  |                 | EC011023 - Tube radiator |
| Material                                                    |                 | Steel                    |
| Material quality                                            |                 | Other                    |
| Number of tubes                                             |                 | 4, 8, 10, 12             |
| Height                                                      | Millimetre (mm) | 955                      |
| Length                                                      | Millimetre (mm) | 476, 676, 776, 876       |
| Depth                                                       | Millimetre (mm) | 216                      |
| Depth from wall to front side min                           | Millimetre (mm) | 116 - 216                |
| Shape of radiation tube                                     |                 | Round                    |
| Shape of collector                                          |                 | Round                    |
| Installation                                                |                 | Vertical                 |
| Radiant tube                                                |                 | Horizontal               |
| Radiator design                                             |                 | Straight                 |
| Towel radiator model                                        |                 | Yes                      |
| Heat emission according to EN 442 20 °C Watt (W)<br>- 55/45 |                 | 226, 322, 370, 419       |
| Heat emission according to EN 442 20 °C Watt (W)<br>- 70/40 |                 | 423, 655, 1187           |
| N-exponent                                                  |                 | 1.2442                   |
| With fan heater                                             |                 | No                       |
| Standard colour                                             |                 | Yes                      |
| Colour                                                      |                 | White                    |
| RAL-number                                                  |                 | 9016                     |
| Degree of gloss                                             |                 | Glossy                   |
| Surface protection                                          |                 | Lacquered                |
| Suitable for damp space                                     |                 | Yes                      |
| With towel holder                                           |                 | No                       |
| With mirror                                                 |                 | No                       |
| Mounting method                                             |                 | On wall                  |
| With side lining                                            |                 | No                       |
| With top cladding                                           |                 | No                       |
| Swivelling                                                  |                 | No                       |
| Applicable with hot tap water circuit                       |                 | No                       |
| Number of standard connections                              |                 | 2                        |
| Connection 1, bottom left                                   |                 | Inlet/outlet flow        |
| Connection 8, bottom right                                  |                 | Inlet/outlet flow        |
| Thread size (inch)                                          |                 | 1/2 inch                 |
| With single-point connection                                |                 | No                       |

| Feature                                                    | Unit                 | Value                  |
|------------------------------------------------------------|----------------------|------------------------|
| Thread connection                                          |                      | Internal thread        |
| With de-aeration connection                                |                      | Yes                    |
| With de-aerator                                            |                      | Yes                    |
| With drain possibility (connection)                        |                      | Yes                    |
| With drain valve                                           |                      | No                     |
| With integrated thermostatic valve                         |                      | No                     |
| With consoles                                              |                      | Yes                    |
| With blind stops                                           |                      | Yes                    |
| With mounting material                                     |                      | Yes                    |
| Mounting Direction                                         |                      | Horizontal             |
|                                                            |                      |                        |
| Heat emission according to EN 442 20 °C<br>– 55/45 [Btu/h] |                      | 771, 1099, 1262, 1430  |
| Max. Operating Temperature                                 | Degrees celsius (°C) | 110                    |
|                                                            |                      |                        |
| Heat emission according to EN 442 20 °C<br>– 75/65 [Btu/h] |                      | 1443, 2054, 2361, 2672 |
| Watt Absolute                                              | Watt (W)             | 423, 602, 692, 783     |
| Weight                                                     | Kilogram (kg)        | 15.6, 21.3, 24.4, 27   |

# Resources

| Document Description                          | Document Type | Link                                                                                                                                                                                                                |
|-----------------------------------------------|---------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Myson Dee Brochure                            | Brochure      | <a href="https://asset.productmarketingcloud.com/api/assetstorage/3577_2b4a432a-0cc5-4f65-97c6-889cb53a74f9">https://asset.productmarketingcloud.com/api/assetstorage/3577_2b4a432a-0cc5-4f65-97c6-889cb53a74f9</a> |
| Myson Complete Solutions - Full Brochure      | Brochure      | <a href="https://asset.productmarketingcloud.com/api/assetstorage/3577_24872a57-c3a5-4956-ab4b-dfa3b522c19b">https://asset.productmarketingcloud.com/api/assetstorage/3577_24872a57-c3a5-4956-ab4b-dfa3b522c19b</a> |
| Myson Towel Warmer Accessory Brochure         | Brochure      | <a href="https://asset.productmarketingcloud.com/api/assetstorage/3577_4fe4000e-8d2d-4051-b8f8-c369afc56a1a">https://asset.productmarketingcloud.com/api/assetstorage/3577_4fe4000e-8d2d-4051-b8f8-c369afc56a1a</a> |
| Myson Traditional Towel Warmer Range Brochure | Brochure      | <a href="https://asset.productmarketingcloud.com/api/assetstorage/3577_142fc909-d562-4ad4-97b1-1f7e115b8e9a">https://asset.productmarketingcloud.com/api/assetstorage/3577_142fc909-d562-4ad4-97b1-1f7e115b8e9a</a> |
| Myson Towel Warmers - range brochure          | Brochure      | <a href="https://asset.productmarketingcloud.com/api/assetstorage/3577_5781fce0-5efe-4895-b2bb-1b6f125c165b">https://asset.productmarketingcloud.com/api/assetstorage/3577_5781fce0-5efe-4895-b2bb-1b6f125c165b</a> |

# Items

| Local Code | Global Item Code | Item Description  |
|------------|------------------|-------------------|
| VR1C       | F6C-MTAVR1C      | 955h x 676w - Dee |
| VR1C4      | F6C-MTAVR1C4     | 955h x 476w - Dee |
| VR2C       | F6C-MTAVR2C      | 955h x 776w - Dee |
| VR3C       | F6C-MTAVR3C      | 955h x 876w - Dee |