Product Data Sheet

12/17/2024

Towel Warmers **Ferlo**UK - Myson



- Stylish design
- Ample room
- White & chrome finish
- Dual fuel options
- Various size options

Description

Myson Ferlo is a premium, curved multirail towel radiator that adds a touch of luxury to any bathroom. Our modern ladder towel radiators are simple, elegant and practical and are designed to achieve the perfect combination of practical towel placement, stylish design and radiant heat output. With its classic design, the Ferlo towel radiator makes a great choice for any project. Ladder rails have become a modern requirement for any bathroom, and we have an extensive range to suit every need. Suitable for hydronic systems (chrome option also suitable for direct system).

Area of Application

The Ferlo towel radiator is ideal for bathrooms where both functionality and design are priority. Suitable for hot water systems, it can be paired with underfloor heating. There's an option to fit a Dual Fuel Heater Kit, expanding its use even when central heating is off.

Selection Criteria

Large range of sizes and heat outputs available, in Chrome. Available as a curved model only.

Basic User Instructions

Install the Ferlo towel radiator with Radiator or Thermostatic Radiator Valves to control room temperature. An MHK Dual Fuel Heater Kit can be added for operation during warmer months without requiring the entire heating system. Ensure that wall brackets, air vent, and plug are properly installed to secure the unit.

Prescription text specifiers

The Ferlo towel radiator is a curved multirail towel warmer made from steel for white models and brass for chrome models. It is ideal for hot water systems and can be paired with underfloor heating. The unit supports a dual fuel heater kit for increased usage flexibility. Standard connections include $2 \times \frac{1}{2}$ " BSP, with integrated air vents. The working pressure is up to 7.4 bar for white and 5.3 bar for chrome models. Certified to BS EN 442 and carrying the CE & UKCA Mark, the Ferlo offers a stylish, practical heating solution with a variety of sizes and finishes to fit any design scheme.

Warranty

For your additional peace of mind, Purmo Group gives the following Warranty against manufacturing defect. Your statutory rights are not affected by this Warranty. Subject as provided below, Purmo Group warrants to the original purchaser at the original installation site that its products will be free from defects in materials and workmanship for the following periods:

- Hydronic Radiators: 10 years from date of purchase.*
- Fan Assisted Radiators (ULOW-E2): 2 years from date of purchase.*
- Fan Convectors: 2 years from date of purchase.
- Hydronic Underfloor Heating: 10 years for the pipe from date of purchase.

• Hydronic Underfloor Heating: 2 years on accessories, actuators, ball valves, controls, expansion vessels, fittings, low loss headers, manifolds, mixer control groups & toolingfrom date of purchase.

- Hydronic Underfloor Heating: 12 months on all pumps from date of purchase.
- Electric Underfloor Heating: 10 years from date of purchase (except programmer & sensor).
- Electric Radiators and Towel Warmers: 2 years from date of purchase.*
- Hydronic Towel Warmers: 5 to 10 years from date of purchase depending on product type.*
- Myson Radiator Valves and Controls: 2 to 5 years from date of purchase, depending on range.

*Products which are exposed to prolonged extreme conditions, such as high humidity or severe cold/condensation, may be subject to deterioration. This is not a result of any manufacturing defect. Products installed in these circumstances will be subject to a warranty period of twelve months only.

The original purchaser's remedy for breach of this Warranty is expressly limited to repair or

replacement of any part or parts found to be defective under conditions of normal service and use during the above Warranty period and does not extend to Purmo Group being liable for any incidental, special or consequential damages or losses whatsoever, such as loss of use of the product, inconvenience or lost profits.

This Warranty does not cover any defect, damage or malfunction in the product which is due to: failure to comply in any respect with Purmo Group's installation, maintenance or operating instructions; faulty storage,

handling, installation or repair; mis-use; neglect; accident; abuse; or general wear and tear. Before this warranty can be activated, the original purchaser will be required to prove, with supporting documentation, the date and place of purchase, as Purmo Group may need to conduct its investigation into

the alleged defect. This should be within 28 days of the date when the defect was discovered or ought to have reasonably discovered the defect.

Purmo Group reserves the right to make a reasonable charge for inspecting and testing any product which is subject to a Warranty claim and the rights conferred by the Warranty are conditional upon the payment of such charge. The charge may be made, at Purmo Group's discretion, either before or after the inspection and testing of the product. In the event that it is established to Purmo Group's reasonable satisfaction that a valid Warranty claim has been made in respect of the product, then any inspection charge which has been paid will be refunded in full by Purmo Group.

Specification

| Feature | Unit | Value |
|---|-----------------|---|
| Etim Class | | EC011023 - Tube radiator |
| Material | | Steel |
| Material quality | | Other |
| Number of tubes | | 13, 22, 35 |
| Height | Millimetre (mm) | 730, 1200, 1858 |
| Length | Millimetre (mm) | 440, 490, 590, 740 |
| Depth | Millimetre (mm) | 120 |
| Depth from wall to front side min | Millimetre (mm) | 58 - 97 |
| Shape of radiation tube | | Round |
| Shape of collector | | Round |
| Installation | | Vertical |
| Radiant tube | | Horizontal |
| Radiator design | | Straight |
| Towel radiator model | | Yes |
| Heat emission according to EN 442 20 ° | C Watt (W) | 103, 114, 137, 157, 163 417, 427, 438, 525, |
| - 55/45 | | 656 |
| Heat emission according to EN 442 20 $^\circ$ | C Watt (W) | 195, 217, 260, 297, 322 818, 821, 839, |
| - 75/65 | | 1006, 1258 |
| Heat emission according to EN 442 20 $^\circ$ | C Watt (W) | 163, 174, 226, 347, 392 926, 933, 1030, |
| - 70/40 | | 1031, 1170 |
| N-exponent | | 1.2321, 1.2334, 1.2476, 1.2547, 1.273, 1.3278 |
| Max. operating pressure | Bar (bar) | 7.4 |
| With fan heater | | No |
| Standard colour | | Yes |
| Colour | | White |
| RAL-number | | 9016 |
| Degree of gloss | | Glossy |
| Surface protection | | Lacquered |
| Suitable for damp space | | Yes |
| With towel holder | | No |
| With mirror | | No |
| Mounting method | | On wall |
| With side lining | | No |
| With top cladding | | No |
| Swivelling | | No |
| Applicable with hot tap water circuit | | No |
| Number of standard connections | | 2 |
| Connection 1, bottom left | | Inlet/outlet flow |
| 4 Product Data Sheet Ferlo 12/17/2024 | | |

4 | Product Data Sheet Ferlo, 12/17/2024

| Feature | Unit | Value |
|--|----------------------|--|
| Connection 8, bottom right | | Inlet/outlet flow |
| Thread size (inch) | | 1/2 inch |
| With single-point connection | | No |
| Thread connection | | Internal thread |
| With de-aeration connection | | Yes |
| With de-aerator | | Yes |
| With drain possibility (connection) | | Yes |
| With drain valve | | No |
| With integrated thermostatic valve | | No |
| With consoles | | Yes |
| Suitable for electrical element | | No |
| With blind stops | | Yes |
| With mounting material | | Yes |
| Mounting direction | | Vertical |
| Factor K | | 4.32, 6.37 |
| Heat emission according to EN 442 20 °C – 55/45 [Btu/h] | | 351, 389, 467, 536, 556 1423, 1457, 1494, 1791, 2238 |
| Max. operating temperature | Degrees celsius (°C) | 110 |
| Number of wall brackets | | 4 |
| Variant | | Curved |
| Heat emission according to EN 442 20 °C – 75/65 [Btu/h] | | 666, 740, 888, 1015, 1098 2789, 2802, 2861, 3433, 4291 |
| Watt Absolute | Watt (W) | 195, 217, 260, 297, 322 818, 821, 839, 1006, 1258 |
| ltem weight | Kilogram (kg) | 8.4, 10.2, 14.3, 15.4, 15.7, 17, 17.3, 24, 25.2, 27.5, 32.2, 39 |

Resources

| Document Description | Document Type | Link |
|---|---------------|--|
| Myson Ferlo Brochure | Brochure | https://asset.productmarketingcloud.co m/api/assetstorage/3577_f8e35b15-e3b 7-4751-b6c5-b8bfda46a47c |
| Myson Complete Solutions - Full Brochure | Brochure | https://asset.productmarketingcloud.co m/api/assetstorage/3577_24872a57-c3a 5-4956-ab4b-dfa3b522c19b |
| Myson Multi-Rail Towel Warmer Range Brochure | Brochure | https://asset.productmarketingcloud.co m/api/assetstorage/3577_1c8c3186-6bc d-490c-814e-295672ea5849 |
| Myson Towel Warmer Accessory Brochure | Brochure | https://asset.productmarketingcloud.co m/api/assetstorage/3577_4fe4000e-8d2 d-4051-b8f8-c369afc56a1a |
| Myson Towel Warmers - range brochure | Brochure | https://asset.productmarketingcloud.co m/api/assetstorage/3577_5781fce0-5efe -4895-b2bb-1b6f125c165b |

ltems

| Local Code | Global Item Code | Item Description |
|------------|------------------|-----------------------------|
| CMR145C | F5Q-MTACMR145C | Chrome 730h x 440w - Ferlo |
| CMR1C | F5Q-MTACMR1C | Chrome 730h x 490w - Ferlo |
| CMR2C | F5Q-MTACMR2C | Chrome 730h x 590w - Ferlo |
| CMR3C | F5Q-MTACMR3C | Chrome 730h x 740w - Ferlo |
| CMR445C | F5Q-MTACMR445C | Chrome 1200h x 440w - Ferlo |
| CMR4C | F5Q-MTACMR4C | Chrome 1200h x 490w - Ferlo |
| CMR5C | F5Q-MTACMR5C | Chrome 1200h x 590w - Ferlo |
| CMR6C | F5Q-MTACMR6C | Chrome 1200h x 740w - Ferlo |
| CMR745C | F5Q-MTACMR745C | Chrome 1858h x 440w - Ferlo |
| CMR7C | F5Q-MTACMR7C | Chrome 1858h x 490w - Ferlo |
| CMR8C | F5Q-MTACMR8C | Chrome 1858h x 590w - Ferlo |
| CMR9C | F5Q-MTACMR9C | Chrome 1858h x 740w - Ferlo |
| CMR145W | F5Q-MTGCMR145W | White 730h x 440w - Ferlo |
| CMR1W | F5Q-MTGCMR1W | White 730h x 490w - Ferlo |
| CMR2W | F5Q-MTGCMR2W | White 730h x 590w - Ferlo |
| CMR3W | F5Q-MTGCMR3W | White 730h x 740w - Ferlo |
| CMR445W | F5Q-MTGCMR445W | White 1200h x 440w - Ferlo |
| CMR4W | F5Q-MTGCMR4W | White 1200h x 490w - Ferlo |
| CMR5W | F5Q-MTGCMR5W | White 1200h x 590w - Ferlo |
| CMR6W | F5Q-MTGCMR6W | White 1200h x 740w - Ferlo |
| CMR745W | F5Q-MTGCMR745W | White 1858h x 440w - Ferlo |
| CMR7W | F5Q-MTGCMR7W | White 1858h x 490w - Ferlo |
| CMR8W | F5Q-MTGCMR8W | White 1858h x 590w - Ferlo |

6 | Product Data Sheet Ferlo, 12/17/2024

| Local Code | Global Item Code | Item Description |
|------------|------------------|----------------------------|
| CMR9W | F5Q-MTGCMR9W | White 1858h x 740w - Ferlo |