

Product Data Sheet

9/1/2024

Thermostatic Radiator Valves & Heads

Decorative TRV Valve Pack

UK - Myson



- Polished chrome finish
- Thermostatic control
- Matching lockshield included
- Angled and straight options available
- Compatible with modern and traditional interiors

Description

Myson offer a selection of polished chrome Decorative TRVs for projects that need that extra special finishing touch with thermostatic control. The Decorative Radpack includes a polished chrome TRV and lockshield, available in straight or angled options.

Area of Application

The Decorative TRV Valve Pack is ideal for heating systems requiring a stylish finish. Suitable for residential rooms, commercial spaces, modern radiators, and towel warmers, it offers thermostatic control, straight and angled options, and is compatible with both compression and pushfit connections.

Selection Criteria

For product selection, refer to our design service or use the quick selection brochure for assistance in choosing the right TRV valve.

Basic User Instructions

Install the Decorative TRV Valve Pack ensuring the TRV is positioned on the radiator's inlet. Ensure all connections are secure and leak-free. Refer to the manual for specific installation steps. Regularly check the valve for optimum performance and clean the polished chrome finish to maintain its appearance.

Prescription text specifiers

Myson's Decorative TRV Valve Pack is designed for heating systems needing a polished finish. Each pack includes a TRV and matching lockshield, both crafted in polished chrome. Available in 15mm and featuring straight or angled options, the TRV offers precise thermostatic control for energy-efficient heating. Valves come with compression and pushfit connections, cater to various installation requirements, and comply with BS 2767-10 standards. With a 2-year guarantee against manufacturing defects, the Decorative TRV Valve Pack ensures both style and function in residential and commercial projects.

Warranty

For your additional peace of mind, Purmo Group gives the following Warranty against manufacturing defect. Your statutory rights are not affected by this Warranty.

Subject as provided below, Purmo Group warrants to the original purchaser at the original installation site that its products will be free from defects in materials and workmanship for the following periods:

- Hydronic Radiators: 10 years from date of purchase.*
- Fan Assisted Radiators (ULOW-E2): 2 years from date of purchase.*
- Fan Convectors: 2 years from date of purchase.
- Hydronic Underfloor Heating: 10 years for the pipe from date of purchase.
- Hydronic Underfloor Heating: 2 years on accessories, actuators, ball valves, controls, expansion vessels, fittings, low loss headers, manifolds, mixer control groups & tooling from date of purchase.
- Hydronic Underfloor Heating: 12 months on all pumps from date of purchase.
- Electric Underfloor Heating: 10 years from date of purchase (except programmer & sensor).
- Electric Radiators and Towel Warmers: 2 years from date of purchase.*
- Hydronic Towel Warmers: 5 to 10 years from date of purchase depending on product type.*
- Myson Radiator Valves and Controls: 2 to 5 years from date of purchase, depending on range.

*Products which are exposed to prolonged extreme conditions, such as high humidity or severe cold/condensation, may be subject to deterioration. This is not a result of any manufacturing defect. Products installed in these circumstances will be subject to a warranty period of twelve months only.

The original purchaser's remedy for breach of this Warranty is expressly limited to repair or replacement of any part or parts found to be defective under conditions of normal service and use

during the above Warranty period and does not extend to Purmo Group being liable for any incidental, special or consequential damages or losses whatsoever, such as loss of use of the product, inconvenience or lost profits.

This Warranty does not cover any defect, damage or malfunction in the product which is due to: failure to comply in any respect with Purmo Group's installation, maintenance or operating instructions; faulty storage,

handling, installation or repair; mis-use; neglect; accident; abuse; or general wear and tear.

Before this warranty can be activated, the original purchaser will be required to prove, with supporting documentation, the date and place of purchase, as Purmo Group may need to conduct its investigation into

the alleged defect. This should be within 28 days of the date when the defect was discovered or ought to have reasonably discovered the defect.

Purmo Group reserves the right to make a reasonable charge for inspecting and testing any product which is subject to a Warranty claim and the rights conferred by the Warranty are conditional upon the payment of such charge. The charge may be made, at Purmo Group's discretion, either before or after the inspection and testing of the product. In the event that it is established to Purmo Group's reasonable satisfaction that a valid Warranty claim has been made in respect of the product, then any inspection charge which has been paid will be refunded in full by Purmo Group.

Specification

Feature	Unit	Value
Etim Class		EC010136 - Radiator stop valve
Housing material		Brass
Surface protection		Chromium-plated
Size of radiator connection		1/2 inch (15)
Size of pipe connection		1/2 inch (15)
Thermostatic adjustment element connection		External thread
Size of thermostatic adjustment element connection		M30 x 1.5
Shape		Right-angled, Straight
With sealing ring		Yes
With straight tailpiece		Yes
With bent tailpiece		No
With compression set		Yes
Pipe diameter compression set	Millimetre (mm)	15
Can be preset		No
Presetting		None
Operation		Thermostatic without button
Suitable for single pipe system		No
Suitable for two pipe system		Yes
Thermostatically prepared		Yes
Reverse direction of flow		Yes
With dust cap		No
Kv value min		-
Automatic flow control		No
Throughflow capacity (min. 10 kPa) min	Litre per hour (L/h)	-
Throughflow capacity (min. 15 kPa) min	Litre per hour (L/h)	-
Shortened construction length		No
Height	Millimetre (mm)	130
Pressure independent		No
Item width	Millimetre (mm)	100
Item depth	Millimetre (mm)	55
Item weight	Kilogram (kg)	0.1644, 0.1904

Resources

Document Description	Document Type	Link
----------------------	---------------	------

Items

Local Code	Global Item Code	Item Description
DECPAK15SC	FDJN10015AAYBHUK1	Decorative Radpack 15mm TRV & Lockshield Pack Straight Polished Chrome
DECPAK15AC	FDJN10015ABYBHUK1	Decorative Radpack 15mm TRV & Lockshield Pack Angle Polished Chrome