

Product Data Sheet

12/17/2024

Thermostatic Radiator Valves & Heads

Decorative Traditional Valves

UK - Myson



- Polished chrome finish.
- Stylish design.
- Variety of options.
- Manual operation.
- Simple installation.

Description

Myson offer a selection of decorative manual valves for projects that need that extra special finishing touch as they are beautifully finished in highly polished chrome. The Decorative Traditional valve adds a touch of style with its tap-like shape, and is available in compression connection, with straight and angle options in 15mm. See also Decorative Modern and Decorative Modern manual valves.

Area of Application

The Decorative Traditional Valves are perfect for high-end residential and boutique commercial projects needing a stylish finishing touch. Suitable for both modern and traditional interiors, they offer compression and pushfit connections, and are available in 15mm with straight or angled orientations.

Selection Criteria

For product selection, refer to our design service, or for quick selection use our brochure.

Basic User Instructions

Install the Decorative Traditional Valves in accordance with local plumbing codes, ensuring the appropriate type of connection (compression or pushfit) is utilized. Regularly check for leaks and ensure the valve is securely tightened. Clean only with a soft cloth and mild detergent to maintain the polished chrome finish. Avoid abrasive cleaners that may damage the finish.

Prescription text specifiers

The Myson Decorative Traditional Valves provide a high-quality, polished chrome manual valve solution ideal for both modern and traditional projects. These valves are available in 15mm sizes with both straight and angled options and feature a durable, highly polished chrome finish. Compatible with compression and pushfit connections, they offer easy manual operation via a wheelhead or lockshield mechanism. The valves are manufactured under ISO 9001:2008 quality management system and conform to BS 2767-10 standards, ensuring reliability and performance. With their elegant design, these valves provide the perfect finishing touch for any high-end residential or boutique commercial project.

Warranty

For your additional peace of mind, Purmo Group gives the following Warranty against manufacturing defect. Your statutory rights are not affected by this Warranty.

Subject as provided below, Purmo Group warrants to the original purchaser at the original installation site that its products will be free from defects in materials and workmanship for the following periods:

- Hydronic Radiators: 10 years from date of purchase.*
- Fan Assisted Radiators (ULOW-E2): 2 years from date of purchase.*
- Fan Convectors: 2 years from date of purchase.
- Hydronic Underfloor Heating: 10 years for the pipe from date of purchase.
- Hydronic Underfloor Heating: 2 years on accessories, actuators, ball valves, controls, expansion vessels, fittings, low loss headers, manifolds, mixer control groups & tooling from date of purchase.
- Hydronic Underfloor Heating: 12 months on all pumps from date of purchase.
- Electric Underfloor Heating: 10 years from date of purchase (except programmer & sensor).
- Electric Radiators and Towel Warmers: 2 years from date of purchase.*
- Hydronic Towel Warmers: 5 to 10 years from date of purchase depending on product type.*
- Myson Radiator Valves and Controls: 2 to 5 years from date of purchase, depending on range.

*Products which are exposed to prolonged extreme conditions, such as high humidity or severe cold/condensation, may be subject to deterioration. This is not a result of any manufacturing defect. Products installed in these circumstances will be subject to a warranty period of twelve months only.

The original purchaser's remedy for breach of this Warranty is expressly limited to repair or

replacement of any part or parts found to be defective under conditions of normal service and use during the above Warranty period and does not extend to Purmo Group being liable for any incidental, special or consequential damages or losses whatsoever, such as loss of use of the product, inconvenience or lost profits.

This Warranty does not cover any defect, damage or malfunction in the product which is due to: failure to comply in any respect with Purmo Group's installation, maintenance or operating instructions; faulty storage,

handling, installation or repair; mis-use; neglect; accident; abuse; or general wear and tear.

Before this warranty can be activated, the original purchaser will be required to prove, with supporting documentation, the date and place of purchase, as Purmo Group may need to conduct its investigation into

the alleged defect. This should be within 28 days of the date when the defect was discovered or ought to have reasonably discovered the defect.

Purmo Group reserves the right to make a reasonable charge for inspecting and testing any product which is subject to a Warranty claim and the rights conferred by the Warranty are conditional upon the payment of such charge. The charge may be made, at Purmo Group's discretion, either before or after the inspection and testing of the product. In the event that it is established to Purmo Group's reasonable satisfaction that a valid Warranty claim has been made in respect of the product, then any inspection charge which has been paid will be refunded in full by Purmo Group.

Specification

Feature	Unit	Value
Etim Class		EC010136 - Radiator stop valve
Housing material		Brass
Surface protection		Chromium-plated
Size of radiator connection		1/2 inch (15)
Size of pipe connection		1/2 inch (15)
Shape		Right-angled, Straight
With sealing ring		Yes
With straight tailpiece		Yes
With bent tailpiece		No
With compression set		Yes
Pipe diameter compression set	Millimetre (mm)	15
Can be preset		No
Presetting		None
Operation		Manually operated
Suitable for single pipe system		No
Suitable for two pipe system		Yes
Thermostatically prepared		No
Reverse direction of flow		Yes
With dust cap		No
Kv value min		-
Automatic flow control		No
Throughflow capacity (min. 10 kPa) min	Litre per hour (l/h)	-
Throughflow capacity (min. 15 kPa) min	Litre per hour (l/h)	-
Shortened construction length		No
Height	Millimetre (mm)	120
Pressure independent		No
Item width	Millimetre (mm)	130
Item depth	Millimetre (mm)	120
Item weight	Kilogram (kg)	0.39, 0.402

Resources

Document Description	Document Type	Link
----------------------	---------------	------

Items

Local Code	Global Item Code	Item Description
DEC15LWSCTRAD	FDII60015AAYBHUK1	Decorative 15mm LS Or Wheelhead Straight Polished Chrome - Traditional
DEC15LWACTRAD	FDII60015ABYBHUK1	Decorative 15mm LS Or Wheelhead Angle Polished Chrome - Traditional